Rollip35_MP

Systeme | 198-264 V AC /180-280 V DC
144 topLED 13 W DC - 14.5 W AC | Modular | CRI 90
C00830BBNZZ



Technische Daten	
Typ	Pendelleuchte
Installationsposition	Decke
Installationsumgebung	Indoor
Lichtquelle	LED
Circuit structure	topLED
Optik	No optic
Light emission direction	downward
Lampe Nennleistung	13 W DC
Gesamtleistung	14.5 W
Lichtstrom (Lichtquelle)	2228 lm
Nominale Eingangsspannung	220 - 240 V AC
Eingangsspannungsbereich	198 - 264 V AC
Frequency	50 - 60 Hz
Ähnlichste Farbtemperatur / Tone	4000 K
Farbwiedergabeindex	90 Ra
Gleichstrom/Gleichspannung	AC
Isolierklasse	1
IP	IP20
Glühdrahtprüfung	850°
Direkte Montage auf normal entflammbaren Oberflächen	Ja
CE	Ja
Einschließlich Driver	Driver
Leuchte dimmbar	DALI-2 - PUSH DIM
Schwenkbarkeit	Nein
Drehbarkeit	Nein
Begehbarkeit	Nein
Überrollbarkeit	Nein
Einschließlich Kabel	Nein
Harzbeschichtung	Nein
Typ Lichtabstrahlung	Einflammig
Nettogewicht	1.1 Kg
Modularity	Modular
Schutz vor elektrostatischen Entladungen	Ja
Schutz vor Stoßspannungen	2 KV
Optiktechnologie	Dot free

Oberfläche Oberfläche Gehäuse	
Material	Aluminiumlegierung 6060
Farbe	Text black RAL9005
Bearbeitungstyp	Pulverbeschichtung mit duroplastischen Pulvern

Linea Light Group reserves the right, without any advance notice, to change the characteristics of their products, as well as the availability of the same at any time. No product, relative technical data, illustrations and information are binding for Linea Light Group. Linea Light Group will not be held liable for any illustration, text and/or translation\ errors. All values indicated are measured values. There is a +/- 10% tolerance for the flow, CCT and power data.

Systeme | 198-264 V AC /180-280 V DC | 144 topLED 13 W DC - 14.5 W AC | Modular | CRI 90 | + C-U200002+1
C00830BBNZZ

Single emission systems for indoor application. The natural white LED light source with a no optic light distribution is composed of 144 topled LEDs with CCT of 4000 K and a CRI 90; the source luminous flux is 2228 lm, with a 171.4 lm/W nominal luminous efficacy.

The device body is made of aluminium alloy 6060 and features a text black ral9005 finish, processed by means of powder coating with thermosetting powders.

The ingress protection degree is IP20; the total weight is of 1.1 kg.

The total absorbed power is 14.5 W

The device features protection class I and can be ceiling-mounted.

Compliant with the EN 60598-1 standard and its specific provisions.

Energieeffizienzklasse
Dieses Produkt enthält 2 Lichtquellen der Energieeffizienzklasse D.

Illuminotechnical Eigenschaften	
Light Output Ratio (LOR)	37 %
Lichtstrom (Lichtquelle)	2228 lm
Leuchten Lichtstrom	836 lm
Consumption	14.5 W
Leuchten Lichtausbeute	57 lm/W
Farbtemperatur	4000 K
Standard Deviation of Colour Matching	3 Step MacAdam
Farbwiedergabeindex	90 Ra
Standardumgebungstemperatur	-20 / +50°C
Typische Temperatur am Glas	40°C

LED Life / Failure Ratio
L70 B10 C0 494435h (at Tj 65 Ta 25)
L80 B10 C0 310287h (at Tj 65 Ta 25)
L90 B10 C0 147586h (at Tj 65 Ta 25)

UGR	
UGR axial	25
UGR transversal	26.7
X=4H | Y=8H	S=0.25H
Reflection factor	70/50/20

OPTICAL	
Optik C90/C270	102°
Optik C0/C180	113°
Light distribution simmetry	Symmetrical 2 assis





Linea Light Group reserves the right, without any advance notice, to change the characteristics of their products, as well as the availability of the same at any time. No product, relative technical data, illustrations and information are binding for Linea Light Group. Linea Light Group will not be held liable for any illustration, text and/or translation\ errors. All values indicated are measured values. There is a +/- 10% tolerance for the flow, CCT and power data.

Systeme | 198-264 V AC /180-280 V DC | 144 topLED 13 W DC - 14.5 W AC | Modular |

CRI 90 | + C-U200002+2

C00830BBNZZ

Single emission systems for indoor application. The natural white LED light source with a no optic light distribution is composed of 144 topled LEDs with CCT of 4000 K and a CRI 90; the source luminous flux is 2228 lm, with a 171.4 lm/W nominal luminous efficacy.

The device body is made of aluminium alloy 6060 and features a text black ral9005 finish, processed by means of powder coating with thermosetting powders.

The ingress protection degree is IP20; the total weight is of 1.1 kg.

The total absorbed power is 14.5 W

The device features protection class I and can be ceiling-mounted.

Compliant with the EN 60598-1 standard and its specific provisions.



Energieeffizienzklasse
Dieses Produkt enthält 2 Lichtquellen der Energieeffizienzklasse D.

Illuminotechnical Eigenschaften	
Light Output Ratio (LOR)	37 %
Lichtstrom (Lichtquelle)	2228 lm
Leuchten Lichtstrom	836 lm
Consumption	14.5 W
Leuchten Lichtausbeute	57 lm/W
Farbtemperatur	4000 K
Standard Deviation of Colour Matching	3 Step MacAdam
Farbwiedergabeindex	90 Ra
Standardumgebungstemperatur	-20 / +50°C
Typische Temperatur am Glas	40°C

LED Life / Failure Ratio
L70 B10 C0 494435h (at Tj 65 Ta 25)
L80 B10 C0 310287h (at Tj 65 Ta 25)
L90 B10 C0 147586h (at Tj 65 Ta 25)

UGR	
UGR axial	25
UGR transversal	26.7
X=4H | Y=8H	S=0.25H
Reflection factor	70/50/20

OPTICAL	
Optik C90/C270	113°
Optik C0/C180	102°
Light distribution simmetry	Symmetrical 2 assis

Linea Light Group reserves the right, without any advance notice, to change the characteristics of their products, as well as the availability of the same at any time. No product, relative technical data, illustrations and information are binding for Linea Light Group. Linea Light Group will not be held liable for any illustration, text and/or translation\ errors. All values indicated are measured values. There is a +/- 10% tolerance for the flow, CCT and power data.

Rollip35_MP | Systems | Accessories
C00830BBNZZ

Diffusor - Asymmetrisch - Länge 1.5m
Diffusorart: asymmetric diffuser.
Material:UV beständiges Polycarbonat, farbe:Opal.

Code
C-U200032



Diffusor - Blendschutzdiffusor UGR kleiner als 19 - Länge 1.5m
Diffusorart: anti-abbagliamento.
Material:UV beständiges Polycarbonat, farbe:Transparent.

Code
C-U200035



Diffusor - Blendschutzdiffusor UGR kleiner als 19 - Länge 2m
Diffusorart: anti-abbagliamento.
Material:UV beständiges Polycarbonat, farbe:Transparent.

Code
C-U200036



Diffusor - Blendschutzdiffusor UGR kleiner als 19 - Länge 3m
Diffusorart: anti-abbagliamento.
Material:UV beständiges Polycarbonat, farbe:Transparent.

Code
C-U200037



Diffusor - Blendschutzdiffusor UGR weniger als 19 – Länge 5 m
Diffusorart: anti-abbagliamento.
Material:UV beständiges Polycarbonat, farbe:Transparent.

Code
C-U200026



Diffusor - Blendschutzdiffusor UGR weniger als 19 – Länge 10m
Diffusorart: anti-abbagliamento.
Material:UV beständiges Polycarbonat, farbe:Transparent.

Code
C-U200027



Diffusor - Asymmetrisch - Länge 2m
Diffusorart: asymmetric diffuser.
Material:UV beständiges Polycarbonat, farbe:Opal.

Code
C-U200033



Diffusor - Asymmetrisch - Länge 3m
Diffusorart: asymmetric diffuser.
Material:UV beständiges Polycarbonat, farbe:Opal.

Code
C-U200034

Linea Light Group reserves the right, without any advance notice, to change the characteristics of their products, as well as the availability of the same at any time. No product, relative technical data, illustrations and information are binding for Linea Light Group. Linea Light Group will not be held liable for any illustration, text and/or translation\ errors. All values indicated are measured values. There is a +/- 10% tolerance for the flow, CCT and power data.

Rollip35_MP | Systems | Accessories
C00830BBNZZ

Diffusor - Asymmetrisch - Länge 5m
Diffusorart: asymmetric diffuser.
Material:UV beständiges Polycarbonat, farbe:Opal.

Code
C-U200006



Diffusor - Asymmetrisch - Länge 10m
Diffusorart: asymmetric diffuser.
Material:UV beständiges Polycarbonat, farbe:Opal.

Code
C-U200007



Diffusor - Opal - Länge 1.5m
Diffusorart: opal diffuser.
Material:UV beständiges Polycarbonat, farbe:Opal.

Code
C-U200029



Diffusor - Opal - Länge 2m
Diffusorart: opal diffuser.
Material:UV beständiges Polycarbonat, farbe:Opal.

Code
C-U200030



Diffusor - Opal - Länge 3m
Diffusorart: opal diffuser.
Material:UV beständiges Polycarbonat, farbe:Opal.

Code
C-U200031

Diffusor - Opal – Länge 5 m
Diffusorart: opal diffuser.
Material:UV beständiges Polycarbonat, farbe:Opal.

Code
C-U200002



Diffusor - Opal – Länge 10m
Diffusorart: opal diffuser.
Material:UV beständiges Polycarbonat, farbe:Opal.

Code
C-U200003



Diffusor - Opal – Länge 20m
Diffusorart: opal diffuser.
Material:UV beständiges Polycarbonat, farbe:Opal.

Code
C-U200004

Linea Light Group reserves the right, without any advance notice, to change the characteristics of their products, as well as the availability of the same at any time. No product, relative technical data, illustrations and information are binding for Linea Light Group. Linea Light Group will not be held liable for any illustration, text and/or translation\ errors. All values indicated are measured values. There is a +/- 10% tolerance for the flow, CCT and power data.

Rollip35_MP | Systems | Accessories
C00830BBNZZ



Endkappe
Material:Stranggepresstes Aluminium EN AB - 46100, farbe:Text black RAL9005, bearbeitungstyp :Pulverbeschichtung mit duroplastischen Pulvern.

Code
C-V400016



Drahtabdeckung
Material:Eisen, farbe:Text black RAL9005, bearbeitungstyp :Pulverbeschichtung mit duroplastischen Pulvern.

Code
63301

Hängeleuchten - Enthält ein einzelnes Aufhängekabel (KIT). Für das Startmodul werden 2 KITS benötigt, für die weiteren Module 1 KIT pro Modul.
Material:Stahl, farbe:Text black RAL9005, bearbeitungstyp :Lackierung.

Code
C-F100021

Linea Light Group reserves the right, without any advance notice, to change the characteristics of their products, as well as the availability of the same at any time. No product, relative technical data, illustrations and information are binding for Linea Light Group. Linea Light Group will not be held liable for any illustration, text and/or translation\ errors. All values indicated are measured values. There is a +/- 10% tolerance for the flow, CCT and power data.