Rollip60_MP

Systeme | 198-264 V AC /180-280 V DC
204 topLED 33 W DC - 36 W AC | Modular | CRI 90
C01295BBNDZ



Technische Daten	
Typ	Pendelleuchte
Installationsposition	Decke
Installationsumgebung	Indoor
Lichtquelle	LED
Circuit structure	topLED
Optik	Diffused + No Optic
Light emission direction	downward and upward
Lampe Nennleistung	33 W DC
Gesamtleistung	36 W
Lichtstrom (Lichtquelle)	5243 lm
Nominale Eingangsspannung	220 - 240 V AC
Eingangsspannungsbereich	198 - 264 V AC
Frequency	50 - 60 Hz
Ähnlichste Farbtemperatur / Tone	4000 K
Farbwiedergabeindex	90 Ra
Gleichstrom/Gleichspannung	AC
Isolierklasse	1
IP	IP20
Glühdrahtprüfung	850°
Direkte Montage auf normal entflammbaren Oberflächen	Ja
CE	Ja
Einschließlich Driver	Driver
Leuchte dimmbar	Nein
Schwenkbarkeit	Nein
Drehbarkeit	Nein
Begehbarkeit	Nein
Überrollbarkeit	Nein
Einschließlich Kabel	Nein
Harzbeschichtung	Nein
Typ Lichtabstrahlung	Zweiflammig
Nettogewicht	1.1 Kg
Modularity	Modular
Schutz vor elektrostatischen Entladungen	Ja
Schutz vor Stoßspannungen	2 KV
Optiktechnologie	Dot free

Oberfläche Oberfläche Gehäuse	
Material	Aluminiumlegierung 6060
Farbe	Text black RAL9005
Bearbeitungstyp	Pulverbeschichtung mit duroplastischen Pulvern

Linea Light Group reserves the right, without any advance notice, to change the characteristics of their products, as well as the availability of the same at any time. No product, relative technical data, illustrations and information are binding for Linea Light Group. Linea Light Group will not be held liable for any illustration, text and/or translation\ errors. All values indicated are measured values. There is a +/- 10% tolerance for the flow, CCT and power data.

Systeme | 198-264 V AC /180-280 V DC | 204 topLED 33 W DC - 36 W AC | Modular | CRI 90 | + CU200008
C01295BBNDZ

Double emission systems for indoor application. The natural white LED light source with a diffused + no optic light distribution is composed of 204 topled LEDs with CCT of 4000 K and a CRI 90; the source luminous flux is 5243 lm, with a 158.9 lm/W nominal luminous efficacy.

The device body is made of aluminium alloy 6060 and features a text black ral9005 finish, processed by means of powder coating with thermosetting powders.

The ingress protection degree is IP20; the total weight is of 1.1 kg.

The total absorbed power is 36 W

The device features protection class I and can be ceiling-mounted.

Compliant with the EN 60598-1 standard and its specific provisions.

Energieeffizienzklasse	

Illuminotechnical Eigenschaften	
Light Output Ratio (LOR)	83 %
Lichtstrom (Lichtquelle)	5243 lm
Leuchten Lichtstrom	4370 lm
Consumption	36 W
Leuchten Lichtausbeute	121 lm/W
Farbtemperatur	4000 K
Standard Deviation of Colour Matching	3 Step MacAdam
Farbwiedergabeindex	90 Ra
Standardumgebungstemperatur	-20 / +50°C
Typische Temperatur am Glas	40°C

LED Life / Failure Ratio
L70 B10 C0 494435h (at Tj 65 Ta 25)
L80 B10 C0 310287h (at Tj 65 Ta 25)
L90 B10 C0 147586h (at Tj 65 Ta 25)

UGR	
UGR axial	21.2
UGR transversal	23.3
X=4H | Y=8H	S=0.25H
Reflection factor	70/50/20

OPTICAL	
Optik C90/C270	108°
Optik C0/C180	129°
Light distribution simmetry	Symmetrical 2 assis





Linea Light Group reserves the right, without any advance notice, to change the characteristics of their products, as well as the availability of the same at any time. No product, relative technical data, illustrations and information are binding for Linea Light Group. Linea Light Group will not be held liable for any illustration, text and/or translation\ errors. All values indicated are measured values. There is a +/- 10% tolerance for the flow, CCT and power data.

Systeme | 198-264 V AC /180-280 V DC | 204 topLED 33 W DC - 36 W AC | Modular | CRI 90 | + CU200012

C01295BBNDZ

Double emission systems for indoor application. The natural white LED light source with a diffused + no optic light distribution is composed of 204 topled LEDs with CCT of 4000 K and a CRI 90; the source luminous flux is 5243 lm, with a 158.9 lm/W nominal luminous efficacy.

The device body is made of aluminium alloy 6060 and features a text black ral9005 finish, processed by means of powder coating with thermosetting powders.

The ingress protection degree is IP20; the total weight is of 1.1 kg.

The total absorbed power is 36 W

The device features protection class I and can be ceiling-mounted.

Compliant with the EN 60598-1 standard and its specific provisions.



Energieeffizienzklasse	

Illuminotechnical Eigenschaften	
Light Output Ratio (LOR)	85 %
Lichtstrom (Lichtquelle)	5243 lm
Leuchten Lichtstrom	4486 lm
Consumption	36 W
Leuchten Lichtausbeute	124 lm/W
Farbtemperatur	4000 K
Standard Deviation of Colour Matching	3 Step MacAdam
Farbwiedergabeindex	90 Ra
Standardumgebungstemperatur	-20 / +50°C
Typische Temperatur am Glas	40°C

LED Life / Failure Ratio
L70 B10 C0 494435h (at Tj 65 Ta 25)
L80 B10 C0 310287h (at Tj 65 Ta 25)
L90 B10 C0 147586h (at Tj 65 Ta 25)

UGR	
UGR axial	21.2
UGR transversal	23.3
X=4H | Y=8H	S=0.25H
Reflection factor	70/50/20

OPTICAL	
Optik C0/C180	80°
Light distribution simmetry	Asymmetrical

Linea Light Group reserves the right, without any advance notice, to change the characteristics of their products, as well as the availability of the same at any time. No product, relative technical data, illustrations and information are binding for Linea Light Group. Linea Light Group will not be held liable for any illustration, text and/or translation\ errors. All values indicated are measured values. There is a +/- 10% tolerance for the flow, CCT and power data.

Systeme | 198-264 V AC /180-280 V DC | 204 topLED 33 W DC - 36 W AC | Modular | CRI 90 | + CU200014

C01295BBNDZ

Double emission systems for indoor application. The natural white LED light source with a diffused + no optic light distribution is composed of 204 topled LEDs with CCT of 4000 K and a CRI 90; the source luminous flux is 5243 lm, with a 158.9 lm/W nominal luminous efficacy.

The device body is made of aluminium alloy 6060 and features a text black ral9005 finish, processed by means of powder coating with thermosetting powders.

The ingress protection degree is IP20; the total weight is of 1.1 kg.

The total absorbed power is 36 W

The device features protection class I and can be ceiling-mounted.

Compliant with the EN 60598-1 standard and its specific provisions.

Energieeffizienzklasse	

Illuminotechnical Eigenschaften	
Light Output Ratio (LOR)	77 %
Lichtstrom (Lichtquelle)	5243 lm
Leuchten Lichtstrom	4071 lm
Consumption	36 W
Leuchten Lichtausbeute	113 lm/W
Farbtemperatur	4000 K
Standard Deviation of Colour Matching	3 Step MacAdam
Farbwiedergabeindex	90 Ra
Standardumgebungstemperatur	-20 / +50°C
Typische Temperatur am Glas	40°C

LED Life / Failure Ratio
L70 B10 C0 494435h (at Tj 65 Ta 25)
L80 B10 C0 310287h (at Tj 65 Ta 25)
L90 B10 C0 147586h (at Tj 65 Ta 25)

UGR	
UGR axial	15.6
UGR transversal	15.8
X=4H | Y=8H	S=0.25H
Reflection factor	70/50/20

OPTICAL	
Optik C90/C270	65°
Optik C0/C180	72°
Light distribution simmetry	Symmetrical 2 assis





Linea Light Group reserves the right, without any advance notice, to change the characteristics of their products, as well as the availability of the same at any time. No product, relative technical data, illustrations and information are binding for Linea Light Group. Linea Light Group will not be held liable for any illustration, text and/or translation\ errors. All values indicated are measured values. There is a +/- 10% tolerance for the flow, CCT and power data.

Rollip60_MP | Systems | Accessories
C01295BBNDZ



Diffusor - Asymmetrisch - Länge 1.5m
Diffusorart: asymmetric diffuser.
Material:UV beständiges Polycarbonat, farbe:Opal.

Code
C-U200038



Diffusor - Asymmetrisch - Länge 2m
Diffusorart: asymmetric diffuser.
Material:UV beständiges Polycarbonat, farbe:Opal.

Code
C-U200039



Diffusor - Asymmetrisch - Länge 3m
Diffusorart: asymmetric diffuser.
Material:UV beständiges Polycarbonat, farbe:Opal.

Code
C-U200040



Diffusor - Asymmetrisch - Länge 5m
Diffusorart: asymmetric diffuser.
Material:UV beständiges Polycarbonat, farbe:Opal.

Code
C-U200012



Diffusor - Asymmetrisch - Länge 10m
Diffusorart: asymmetric diffuser.
Material:UV beständiges Polycarbonat, farbe:Opal.

Code
C-U200013



Diffusor - Opal - Länge 1.5m
Diffusorart: opal diffuser.
Material:UV beständiges Polycarbonat, farbe:Opal.

Code
C-U200041



Diffusor - Opal - Länge 2m
Diffusorart: opal diffuser.
Material:UV beständiges Polycarbonat, farbe:Opal.

Code
C-U200042



Diffusor - Opal - Länge 3m
Diffusorart: opal diffuser.
Material:UV beständiges Polycarbonat, farbe:Opal.

Code
C-U200043

Linea Light Group reserves the right, without any advance notice, to change the characteristics of their products, as well as the availability of the same at any time. No product, relative technical data, illustrations and information are binding for Linea Light Group. Linea Light Group will not be held liable for any illustration, text and/or translation\ errors. All values indicated are measured values. There is a +/- 10% tolerance for the flow, CCT and power data.

Rollip60_MP | Systems | Accessories
C01295BBNDZ



Diffusor - Opal – Länge 5 m
Diffusorart: opal diffuser.
Material:UV beständiges Polycarbonat, farbe:Opal.

Code
C-U200008



Diffusor - Opal – Länge 10m
Diffusorart: opal diffuser.
Material:UV beständiges Polycarbonat, farbe:Opal.

Code
C-U200009



Diffusor - Opal – Länge 20m
Diffusorart: opal diffuser.
Material:UV beständiges Polycarbonat, farbe:Opal.

Code
C-U200010



Diffusor - Blendfreier Diffusor – Länge 1.5m
Diffusorart: anti-glare diffuser.
Material:UV beständiges Polycarbonat, farbe:Opal, bearbeitungstyp :Satinieren.

Code
C-U200044



Diffusor - Blendfreier Diffusor – Länge 2m
Diffusorart: anti-glare diffuser.
Material:UV beständiges Polycarbonat, farbe:Opal, bearbeitungstyp :Satinieren.

Code
C-U200045



Diffusor - Blendfreier Diffusor – Länge 3m
Diffusorart: anti-glare diffuser.
Material:UV beständiges Polycarbonat, farbe:Opal, bearbeitungstyp :Satinieren.

Code
C-U200046



Diffusor - Blendfreier Diffusor – Länge 5m
Diffusorart: anti-glare diffuser.
Material:UV beständiges Polycarbonat, farbe:Opal, bearbeitungstyp :Satinieren.

Code
C-U200014



Diffusor - Blendfreier Diffusor – Länge 10m
Diffusorart: anti-glare diffuser.
Material:UV beständiges Polycarbonat, farbe:Opal, bearbeitungstyp :Satinieren.

Code
C-U200015

Linea Light Group reserves the right, without any advance notice, to change the characteristics of their products, as well as the availability of the same at any time. No product, relative technical data, illustrations and information are binding for Linea Light Group. Linea Light Group will not be held liable for any illustration, text and/or translation\ errors. All values indicated are measured values. There is a +/- 10% tolerance for the flow, CCT and power data.

Rollip60_MP | Systems | Accessories
C01295BBNDZ





Endkappe
Material:Stranggepresstes Aluminium EN AB - 46100, farbe:Text black RAL9005, bearbeitungstyp :Pulverbeschichtung mit duroplastischen Pulvern.

Code
C-V400018



Drahtabdeckung
Material:Eisen, farbe:Text black RAL9005, bearbeitungstyp :Pulverbeschichtung mit duroplastischen Pulvern.

Code
63300

Hängeleuchten - Enthält ein einzelnes Aufhängekabel (KIT). Für das Startmodul werden 2 KITS benötigt, für die weiteren Module 1 KIT pro Modul.
Material:Stahl, farbe:Text black RAL9005, bearbeitungstyp :Lackierung.

Code
C-F100021

Linea Light Group reserves the right, without any advance notice, to change the characteristics of their products, as well as the availability of the same at any time. No product, relative technical data, illustrations and information are binding for Linea Light Group. Linea Light Group will not be held liable for any illustration, text and/or translation\ errors. All values indicated are measured values. There is a +/- 10% tolerance for the flow, CCT and power data.