



Deckenleuchten | 198-264 V
72 topLED 25 W DC - 27 W AC | CRI 90
CA050DLUWDI



Technische Daten	
Typ	Deckenleuchten
Installationsposition	Decke
Installationsumgebung	Indoor
Lichtquelle	LED
Circuit structure	topLED
Optik	Diffuses
Light emission direction	downward
Lampe Nennleistung	25 W DC
Gesamtleistung	27 W
Lichtstrom (Lichtquelle)	3410 lm
Nominale Eingangsspannung	220 - 240 V AC
Eingangsspannungsbereich	198 - 264 V AC
Frequency	50 - 60 Hz
Ähnlichste Farbtemperatur / Tone	3000 K
Farbwiedergabeindex	90 Ra
Gleichstrom/Gleichspannung	AC
Isolierklasse	1
IP	IP20
Glühdrahtprüfung	850°
Direkte Montage auf normal entflammaren Oberflächen	Ja
CE	Ja
Einschließlich Driver	Driver
Leuchte dimmbar	Phase cut
Schwenkbarkeit	Nein
Drehbarkeit	Nein
Begehbarkeit	Nein
Überrollbarkeit	Nein
Einschließlich Kabel	Nein
Harzbeschichtung	Nein
Typ Lichtabstrahlung	Einflammig
Schutz vor elektrostatischen Entladungen	Ja
Schutz vor Stoßspannungen	2 KV

Oberfläche Oberfläche Gehäuse

Material	Aluminium
Farbe	Text deep blue (R5011)
Bearbeitungstyp	Lackierung

Oberfläche Oberfläche diffusor

Material	PMMA
Farbe	Opal

Oberfläche Oberfläche fassung

Material	Eisen
Farbe	Text deep blue (R5011)
Bearbeitungstyp	Lackierung

Deckenleuchten | 198-264 V | 72 topLED 25 W DC - 27 W AC | CRI 90
CA050DLUWDI

Single emission ceiling downlights for indoor application. The warm white LED light source with a diffused light distribution is composed of 72 topLEDs with CCT of 3000 K and a CRI 90; the source luminous flux is 3410 lm, with a 136.4 lm/W nominal luminous efficacy.

The device body is made of aluminium and features a text deep blue (r5011) finish, processed by means of coating; the diffuser is made of pmma; the mounting frame is made of iron, with a text deep blue (r5011) finish, processed by means of coating.


The ingress protection degree is IP20;

The total absorbed power is 27 W

The device features protection class I and can be ceiling-mounted.

Compliant with the EN 60598-1 standard and its specific provisions.

Illuminotechnical Eigenschaften	
Light Output Ratio (LOR)	64 %
Lichtstrom (Lichtquelle)	3410 lm
Leuchten Lichtstrom	2215 lm
Consumption	27 W
Leuchten Lichtausbeute	82 lm/W
Farbtemperatur	3000 K
Standard Deviation of Colour Matching	3 Step MacAdam
Farbwiedergabeindex	90 Ra
Standardumgebungstemperatur	-20 / +50°C
LED Life / Failure Ratio	
L70 B10 C0 102000h (at Tj 115 Ta 25)	
L90 B10 C0 55000h	
UGR	
UGR axial	23.7
UGR transversal	23.6
X=4H Y=8H	S=0.25H
Reflection factor	70/50/20
OPTICAL	
Optik C0/C180	147°
Light distribution simmetry	Symmetrical




Distance [m]	Cone diameter [m]	Illuminance [lx]
0.5	3.44 3.42	E(0°) 2140 E(C90) 23 E(C0) 24
1.0	6.88 6.84	E(0°) 535 E(C90) 6 E(C0) 6
1.5	10.33 10.26	E(0°) 238 E(C90) 3 E(C0) 3
2.0	13.77 13.68	E(0°) 134 E(C90) 1 E(C0) 1
2.5	17.21 17.10	E(0°) 86 E(C90) 1 E(C0) 1
3.0	20.65 20.52	E(0°) 59 E(C90) 1 E(C0) 1

Distance [m] Cone diameter [m] Illuminance [lx]


— C0/C180 (Half-peak divergence: 147.4°)
— C90/C270 (Half-peak divergence: 147.6°)

Basin_S | Ceiling Downlights | Accessories
CA050DLUWDI



Dimmer - Phasenabschnitt (max. 100 W) – wichtig zum Dimmen der Lampe
220-240V

Code
KIT0026



Dimmer - Phasenabschnitt, CASAMBI - Unverzichtbar zum Dimmen der Lampe mit Casambi
Radio-frequenza, 85-240V

Code
KIT0080