



STELLA Spot LED Basse Luminance 700lm

Downlight, 3CCT 2700K+3000K+4000K, 7W 700lm, White, Traic Dim, IP44

Model No.: LUSTE04
SGSO Sku: 0017440127
GTIN/EAN: 7630268410469

Suitable for built-in mounting:	Yes
Adjustability:	Not adjustable
Lamp type:	LED not exchangeable
With light source:	Yes
Suitable for number of lamps:	1
Lamp holder:	Other
Material housing:	Aluminium
Colour housing:	White
Material cover:	Other
Voltage type:	AC
Nominal voltage:	220 ... 240 V
LED nominal current at constant current:	200 mA
Type of control gear:	LED operating device current-controlled
With control gear:	Yes
Dimming phase cut-off:	Yes
Dimming phase cut-on:	Yes
Beam angle:	Medium beam 21-40°
Light outlet:	Direct
Energy efficiency class of the built-in lamp:	Other
Rated life time L70/B50 at 25 °C:	50000 h
Rated life time L80/B10 at 25 °C:	30000 h
Degree of protection (IP):	IP44
Impact strength:	IK02
Protection class:	II
Rated ambient temperature according to IEC62722-2-1:	-20 ... 40 °C
Suitable for lamp power:	7 W
Max. system power:	7 W
Colour of light:	White
Colour temperature:	2700 ... 4000 K
Colour rendering index CRI:	80-89
Luminous flux:	700 lm
Rated luminous flux according to IEC 62722-2-1:	700 lm
Power factor:	0.9
Height/depth:	83 mm
Outer diameter:	85 mm
Filament test according to IEC 60695-2-11:	650 °C - 30 s
Luminaire efficacy:	100 lm/W
Colour consistency (McAdam ellipse):	SDCM4

