



PANNELLO SIDE LED 4100lm

Sidelit Big Panel 34W, 4100lm 40K, CRI $\geq$ 80, UGR19 On/-off

Model No.: APAN60S19N
SGSO Sku: 0028920038
GTIN/EAN: 7630268405281

Suitable for ceiling mounting:	Yes
Suitable for built-in mounting:	Yes
Suitable for workplace according to EN 12464-1:	Yes
Lamp type:	LED not exchangeable
With light source:	Yes
Suitable for number of lamps:	1
Lamp holder:	Other
Material housing:	Aluminium
Colour housing:	White
Material cover:	Plastic, structured
Voltage type:	AC
Nominal voltage:	220 ... 240 V
Nominal current:	900 mA
Type of control gear:	LED operating device current--
With control gear:	yes
No dim function:	Yes
Light distributor:	Diffuser lens/optic/panel
Light sharing:	Symmetric
Beam angle:	Extreme wide beam >80°
Colour consistency (McAdam ellipse):	SDCM3
Energy efficiency class of the built-in lamp:	Other
Rated life time L70/B50 at 25 °C:	50000 h
Degree of protection (IP):	IP20
Impact strength:	IK03
Protection class:	II
Rated ambient temperature according to IEC62722-2-1:	-20 ... 40 °C
Filament test according to IEC 60695-2-11:	650 °C - 30 s
Suitable for lamp power:	34 W
Max. system power:	34 W
Luminaire efficacy:	120 lm/W
Rated luminous flux according to IEC 62722-2-1:	4100 lm
Colour of light:	White
Colour temperature:	4000 K
Colour rendering index CRI:	80-89
Power factor:	0.9
Width:	595 mm
Height/depth:	11 mm
Length:	595 mm
Unified Glare Ratio (UGR):	19

