**Informazioni tecniche:**

Installazione:	Soffitto
Materiale Corpo:	Polycarbonato
Finitura:	Verde RAL 6003
Tipo di diffusore:	Polycarbonato
Tipo lampada:	LED
Classe energetica:	F
Temperatura colore:	2700K
CRI:	>80
LB Factor:	L80B50 - 50.000h
Rischio fotobiologico:	RG0
Potenza assorbita Watt:	5
Lumen:	600
Real Lumen:	362
Alimentazione:	✓ integrata
LED:	AC DIRECT
Classe di isolamento:	⊕ CL.I
Grado di protezione:	IP 65
Resistenza alla rottura:	IK 06 1J xx3
Marchi di Conformità:	CE UK
Dimmerazione	Taglio di fase

Versione GU10: lampadina non inclusa.



Clic Top

LL14801V2

Lombardo.



Immagini di montaggio:



Lombardo S.r.l.

Via Pizzigoni 3, Villongo (BG) - 24060 - Italy - T 0039 035 939 411 - E info@lombardo.it

lombardo.it

The diagram illustrates a lighting fixture (represented by a black dot) positioned at a height of 2,8m above a grid. The grid is composed of squares, each measuring 0,5m by 0,5m. A color-coded legend indicates the Lux levels (LUX) corresponding to the colors of the grid cells:

- 150,00 (Dark Red)
- 50,00 (Red)
- 25,00 (Orange)
- 10,00 (Light Orange)
- 0,00 (White)

The fixture is positioned such that its light distribution is centered on the grid, with the highest intensity (150,00 Lux) directly beneath it, decreasing as the distance from the fixture increases.

clac_top