



Caratteristiche elettriche

Corrente d'impiego max ($\leq 440V$) A 9

Caratteristiche dei contatti

Corrente di impiego Ie AC-3 ($\leq 440V \leq 55^{\circ}C$) A 9

Potenza nominale AC-3 ($T \leq 55^{\circ}C$)	Voltage	Power (kW)
	230V	2.2
	400V	4
	415V	4.3
	440V	4.5
	500V	5
	690V	5

Contatti ausiliari incorporati

NA	0
NC	1

Dati tecnici UL


Maximum UL/CSA horsepower ratings single-phase	Voltage	HP
	110V-120V	0.5
	220V-240V	1.5

Maximum UL/CSA horsepower ratings three-phase, 3-pole	Voltage	HP
	200V-208V	2
	220V-240V	3
	440V-480V	5
	550V-600V	5


Caratteristiche meccaniche

Attacchi tipo	Vite di fissaggio
Peso prodotto	g 394

Dimensioni



Schemi elettrici



Omologazioni e conformità

Conformità

IEC/EN 60947-1
IEC/EN 60947-4-1
UL508 CSA C22.2 n° 14

Omologazioni

cULus

Classificazione ETIM

ETIM 8.0

EC001037 -
Combinazione
starter motore