



Contact characteristics

Number of poles	Nr.	3
Rated insulation voltage U_i IEC/EN	V	1000
Rated impulse withstand voltage U_{imp}	kV	8
Operational frequency	min	Hz 25
	max	Hz 400
IEC Conventional free air thermal current $I_{th} \leq 40^\circ\text{C}$	A	115
IEC max current I_e in DC1 with $L/R \leq 1\text{ms}$ with 3 poles in series	400V	A 100
	600V	A 80
	800V	A 65
	1000V	A 60
Short-time allowable current for 10s (IEC/EN60947-1)	A	640
Protection fuse	gG (IEC)	A 125
	aM (IEC)	A 80
Resistance per pole (average value)	mΩ	0.6
Power dissipation per pole (average value)	I_{th}	W 7.9
Tightening torque for terminals	min	Nm 4
	max	Nm 5
	min	lbin 2.95
	max	lbin 3.69
Tightening torque for coil terminal	min	Nm 0.8
	max	Nm 1
	min	lbin 0.8
	max	lbin 0.74
Max number of wires simultaneously connectable	Nr.	2
Conductor section	AWG/Kcmil	
	max	2
Flexible w/o lug conductor section	min	mm ² 1.5
	max	mm ² 35
Flexible c/w lug conductor section	min	mm ² 1.5
	max	mm ² 35
Power terminal protection according to IEC/EN 60529		IP20 front

Mechanical features

Operating position	normal allowable	Vertical plan $\pm 30^\circ$
--------------------	---------------------	---------------------------------

Fixing			Screw / DIN rail 35mm		
Weight	g		1240		
Operations					
Mechanical life	cycles		15000000		
Safety related data					
Performance level B10d according to EN/ISO 13489-1					
	mechanical load	cycles	15000000		
EMC compatibility			yes		
AC coil operating					
Rated AC voltage at 60Hz	V		48		
AC operating voltage					
of 60Hz coil powered at 60Hz					
	pick-up		min	%Us	80
			max	%Us	110
drop-out					
			min	%Us	20
			max	%Us	55
AC average coil consumption at 20°C					
of 60Hz coil powered at 60Hz					
	in-rush	VA	210		
	holding	VA	15		
Dissipation at holding ≤20°C 50Hz	W		5		
Max cycles frequency					
Mechanical operation	cycles/h		3600		
Operating times					
Average time for Us control					
in AC					
	Closing NO		min	ms	12
			max	ms	28
	Opening NO		min	ms	8
			max	ms	22
in DC					
	Closing NO		min	ms	40
			max	ms	85
	Opening NO		min	ms	20
			max	ms	55
UL technical data					
Rated operational voltage AC (UL)	V		600		
General USE					
Contactor					
	AC current	A	115		
4 poles in series DC1					
	600V	A	100		
Ambient conditions					
Temperature					
Operating temperature					
	min	°C	-50		
	max	°C	70		

Storage temperature

min	°C	-60
max	°C	80

Max altitude


m	3000
---	------

Resistance & Protection



Pollution degree

3

Dimensions



Wiring diagrams



Certifications and compliance

Compliance

CSA C22.2 n° 60947-1

CSA C22.2 n° 60947-4-1

IEC/EN/BS 60947-1

IEC/EN/BS 60947-4-1

UL 60947-1

UL 60947-4-1

ETIM classification

ETIM 8.0

EC002552 -
Power contactor,
DC switching