



Contact characteristics

IEC Conventional free air thermal current $I_{th} \leq 40^{\circ}\text{C}$	A	160
Rated insulation voltage U_i IEC/EN	V	1000
Rated impulse withstand voltage U_{imp}	kV	12
Operating current I_e		
AC21A		
	400V	A 160
	500V	A 160
	690V	A 160
AC22A		
	400V	A 160
	500V	A 160
	690V	A 160
AC23A		
	400V	A 160
	500V	A 160
	690V	A 160
Power dissipation per pole max	W	4
Rated operational power AC23A		
	400V	kW 90
	690V	kW 134
Reactive power for control of capacitors at		
Rated short time current (1s) I_{cw} (rms)	kA	6
Rated short time current (0.3s) I_{cw} (rms)	kA	12
Conditional short-circuit current (rms)	kA	100
Short-circuit protection with fuse	Class/A	gG/160
Making capacity AC23A 400V	A	1600
Breaking capacity AC23A 400V	A	1280
Mechanical life	cycles	20000

Mechanical features

Operating position	normal allowable	Vertical plan Any
Fixing		Screw / DIN rail 35mm
Terminals	type	M8 x 25
Tightening torque for terminals		
	min	Nm 15
	max	Nm 22
	min	lbin 132
	max	lbin 194
Conductor section		
	IEC min	mm ² 70
	IEC max	mm ² 185

AWG/kcmil min	00
AWG/kcmil max	kcmil 400


UL technical data

UL Standard		UL98
General purpose current rating	A	100
Operating voltage max	V	600
Horsepower/FLA current three phase motor		
	240V	HP/A 30/80
	480V	HP/A 75/96
	600V	HP/A 100/99
Short circuit rating	kA rms	200
Short circuit rating with fuse	Class/A	J/100
UL Terminal kit lugs		GLX500 - GLX501
Minimum enclosure dimensions at rated current		
	mm	mm
	in	in
		400 x 250 x 150
		15.8 x 9.9 x 5.9


Ambient conditions

Operating temperature			
	min	°C	-25
	max	°C	+55
Storage temperature			
	min	°C	-40
	max	°C	+70
Max altitude		m	3000

Dimensions



Wiring diagrams



Certifications and compliance

Compliance

IEC/EN 60947-1
IEC/EN 60947-3

Certifications

cULus

ETIM classification

ETIM 8.0

EC000216 -
Switch
disconnecter