# GX2055P

ENCLOSED ROTARY CAM SWITCH GX SERIES, CHANGEOVER SWITCH WITHOUT 0, 2 POLES 20A IN PLASTIC ENCLOSURE 90X90MM WITH BLACK HANDLE

## General characteristics

| | |
|---|---|
| Switching diagram | 55 - Changeover switch without 0 2 poles |
| N° of elements | 2 |
| Mounting form | P - Plastic enclosure with black handle |

## Contact characteristics

| | | | |
|---|---|---|---|
| Rated insulation voltage Ui | | | |
| | IEC/EN | V | 690 |
| | UL/CSA | V | 600 |
| Rated impulse withstand voltage Uimp | | kV | 6 |
| Conventional free air thermal current Ith | | | |
| | IEC/EN | A | 20 |
| | UL/CSA | A | 15 |
| Rated operational voltage | | V | 440 |
| Rated operational impulse voltage | | kV | 4 |
| Maximum fuse size for short-circuit protection In (gG) | | | |
| | 10kA | A | 20 |
| | 15kA | A | 20 |
| | 25kA | A | 20 |
| Rated short time current Icw | | | |
| | 1s | kA | 250 |
| Conductivity | | | 10/5 mA/V |
| Operational current Ie IEC/EN | | | |
| AC1/AC21A | | | |
| | | A | 20 |
| AC15 | | | |
| | 110V | A | 10 |
| | 220/230V | A | 8 |
| | 380/400V | A | 6 |
| | 660/690V | A | 1.5 |
| Rated operational power in AC | | | |
| Three-phase AC-3 | | | |
| | 220/230V | kW | 3.7 |
| | 380/440V | kW | 5.5 |
| | 500/690V | kW | 5.5 |
| Single-phase AC-3 | | | |
| | 110V | kW | 0.75 |
| | 220/230V | kW | 1.8 |
| | 380/440V | kW | 3 |
| Three-phase AC23A | | | |
| | 220/230V | kW | 4 |
| | 380/440V | kW | 7.5 |
| | 500/690V | kW | 7.5 |
| Single-phase AC23A | | | |
| | 110V | kW | 0.75 |
| | 220/230V | kW | 2.2 |
| | 380/440V | kW | 3.5 |
| Rated operational current in DC | | | |
| DC21A | | | |
| | 48V | A | 20 |


The characteristics described in this document are subject to updates or modifications at any time. The descriptions, technical and functional information, illustrations and instructions in this brochure are purely illustrative, and are consequently not contractually binding

| | | | | |
|---|---|---|---|---|
| | | 60V | A | 20 |
| | | 110V | A | 4 |
| | | 220V | A | 0.6 |
| | | 440V | A | 0.25 |
| | DC23A (poles in series) | | | |
| | | 24V | A | 20 (1) |
| | | 48V | A | 20 (2) |
| | | 60V | A | 20 (3) |
| | | 110V | A | 10 (3) |
| | | 220V | A | 8 (4) |
| | DC13 | | | |
| | | 24V | A | 20 |
| | | 48V | A | 16 |
| | | 60V | A | 12 |
| | | 110V | A | 1 |
| | | 220V | A | 0.4 |
| | | 440V | A | 0.15 |
| Power dissipation | | | W | 0.6 |
| **Mechanical features** | | | | |
| Terminals screw | | | | M3 |
| Tightening torque for terminals max | | | Nm | 0.8 |
| Conductor size | | | | |
| | AWG - Rigid cable | | | |
| | | min | AWG | 20 |
| | | Max | AWG | 12 |
| | AWG - Flexible cable | | | |
| | | min | AWG | 20 |
| | | Max | AWG | 12 |
| | Conductor size (IEC) - Flexible cable | | | |
| | | min | mm² | 0.5 |
| | | Max | mm² | 2.5 |
| | Conductor size (IEC) - Rigid cable | | | |
| | | min | mm² | 0.5 |
| | | Max | mm² | 2.5 |
| Mechanical life | | | cycles | $1X10^6$ |
| **UL technical data** | | | | |
| Motor power for direct-on-line control | | | | |
| | for three-phase motor | | | |
| | | 120V | HP | 1.5 |
| | | 240V | HP | 3 |
| | | 480V | HP | 5 |
| | | 600V | HP | 5 |
| | for single-phase motor | | | |
| | | 120V | HP | 0.75 |
| | | 240V | HP | 1.5 |
| **Ambient conditions** | | | | |
| Temperature | | | | |
| | Operating temperature | | | |
| | | min | °C | -25 |
| | | max | °C | +55 |
| | Storage temperature | | | |
| | | min | °C | -40 |
| | | max | °C | +70 |
| **Resistance & Protection** | | | | |



The characteristics described in this document are subject to updates or modifications at any time. The descriptions, technical and functional information, illustrations and instructions in this brochure are purely illustrative, and are consequently not contractually binding

# GX2055P

ENCLOSED ROTARY CAM SWITCH GX SERIES, CHANGEOVER SWITCH WITHOUT 0, 2 POLES 20A IN PLASTIC ENCLOSURE 90X90MM WITH BLACK HANDLE


| | |
|---|---|
| Frontal IP degree | IP65 |
| Terminals IP degree | IP20 |

## Dimensions



| Series | Enclosure size | Number of elements L | Number of elements L1 | Dimensions A | A1 | C | C1 | D | F | M | N | L | L1 | Cable entry | Protection degree |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| GX15●● | 90x90 | 1 - 2 | 3 - 5 | 90 | 90 | 79 | 79 | 4.5 | 25 | 19 | 30 | 71.3 | 98.3 | 4xPG16 | IP65 |
| GX20●● | | 1 - 2 | 3 - 5 | | | | | | | | | | | | |
| GX16 | 110x110 | 1 - 3 | 4 - 7 | 110 | 110 | 98.4 | 83 | 4.5 | 32 | 21 | 39.5 | 85.5 | 119.5 | 4xPG21 | IP65 |
| GX20 | | 1 - 3 | 4 - 7 | | | | | | | | | | | | |
| GX32●● | | 1 - 2 | 3 - 4 | | | | | | | | | | | | |
| GX40●● | | 1 - 2 | 3 - 4 | | | | | | | | | | | | |

## Wiring diagrams




## Certifications and compliance

| | |
|---|---|
| Compliance | |
| | IEC/EN/BS 60947-1 |
| | IEC/EN/BS 60947-3 |
| | IEC/EN/BS 60947-5-1 |
| | IEC/EN/BS 61058-1 |
| Certificates | |
| | EAC |

## ETIM classification

| | |
|---|---|
| ETIM 8.0 | EC001029 - Selector switch, complete |


The characteristics described in this document are subject to updates or modifications at any time. The descriptions, technical and functional information, illustrations and instructions in this brochure are purely illustrative, and are consequently not contractually binding