GX3211U25

ŁĄCZNIK KRZYWKOWY SERII GX, PRZEŁĄCZNIK ZMIANY KIERUNKU OBROTÓW SILNIKA 3 FAZOWEGO, 32A, DO MONTAŻU TABLICOWEGO, Z ŻÓŁTO/CZERWONYM POKRĘTŁEM BLOKOWANYM W POZYCJI 0, OSŁONAMI ZACISKÓW I TABLICZKĄ 65X65MM

Charakterystyka ogólna

Schemat przełączenia	11 - Przełącznik zmiany kierunku obrotów silnika 3 fazowego
N° of elements	3
Rodzaj montażu	U25 - wersja do montażu tablicowego z żółto/czerwonym pokrętłem blokowanym w pozycji 0 i osłonami zacisków

Właściwości styków

Znamionowe napięcie izolacji Ui			
	IEC/EN	V	690
	UL/CSA	V	600
Znamionowe napięcie udarowe Uimp		kV	6
Prąd cieplny umowny Ith			
	IEC/EN	A	32
	UL/CSA	A	32
Znamionowe napięcie robocze		V	440
Znamionowe napięcie udarowe		kV	4
Maksymalna wartość bezpiecznika (gG) do ochrony zwarciowej In			
	10 kA	A	35
	15 kA	A	35
	25 kA	A	35
Prąd udarowy wytrzymywany Icw			
	1 s	kA	1000
Przewodność			10/5 mA/V
Prąd roboczy Ie IEC/EN			
AC1/AC21A			
		A	32
AC15			
	110 V	A	25
	220/230 V	A	20
	380/400 V	A	10
	660/690 V	A	2
Znamionowa moc robocza w AC			
Trójfazowy AC-3			
	220/230 V	kW	7.5
	380/440 V	kW	11
	500/690 V	kW	11
Jednofazowy AC-3			
	110 V	kW	1.8
	220/230 V	kW	3.5
	380/440 V	kW	5.5
Trójfazowy AC23A			
	220/230 V	kW	8
	380/440 V	kW	15
	500/690 V	kW	15
Jednofazowy AC23A			

The characteristics described in this document are subject to updates or modifications at any time. The descriptions, technical and functional information, illustrations and instructions in this brochure are purely illustrative, and are consequently not contractually binding

		110 V	kW	2.2
		220/230 V	kW	3.5
		380/440 V	kW	6
Znamionowy prąd roboczy w DC				
	DC21A			
		48 V	A	32
		60 V	A	32
		110 V	A	5
		220 V	A	0.8
		440 V	A	0.25
	DC23A (pola szeregowo)			
		24 V	A	32 (1)
		48 V	A	32 (2)
		60 V	A	32 (3)
		110 V	A	15 (3)
		220 V	A	12 (4)
	DC13			
		24 V	A	32
		48 V	A	25
		60 V	A	14
		110 V	A	3
		220 V	A	0.5
		440 V	A	0.15
Rozproszenie mocy			W	1.6
Właściwości mechaniczne				
Zacisk śrubowy				M4
Moment obrotowy dokręcania zacisków maks.			Nm	1.2
Rozmiar przewodu				
	AWG - Przewód sztywny			
		min.	AWG	16
		maks.	AWG	8
	AWG - Przewód elastyczny			
		min.	AWG	16
		maks.	AWG	10
	Przekrój przewodu (IEC) - Przewód elastyczny			
		min.	mm²	1.5
		maks.	mm²	6
	Przekrój przewodu (IEC) - Przewód sztywny			
		min.	mm²	1.5
		maks.	mm²	10
Trwałość mechaniczna			cycles	1X10⁶
Dane techniczne UL				
Sterowanie bezpośrednie silnika (UL/CSA-DOL)				
	dla trójfazowego silnika			
		120 V	HP	3
		240 V	HP	7.5
		480 V	HP	15
		600 V	HP	15
	dla jednofazowego silnika			
		120 V	HP	1.5
		240 V	HP	3
Warunki otoczenia				
Temperatura				
	Temperatura pracy			


The characteristics described in this document are subject to updates or modifications at any time. The descriptions, technical and functional information, illustrations and instructions in this brochure are purely illustrative, and are consequently not contractually binding

	min.	°C	-25
	maks.	°C	+55
Temperatura składowania			
	min.	°C	-40
	maks.	°C	+70

Odporność i zabezpieczenie

Stopień ochrony IP od frontu	IP65
Stopień ochrony IP zacisków	IP20


Wymiary



Drillings for 4 screws fixing (4V version).

Series	Dimensions						L			
	□A	D1	D2	E	G	□K	1	2	3.....12	
GX16	48	12	5	34.2	5	36	43	51.5	60	136.5
GX20	48	12	5	34.2	5	36	43	51.5	60	136.5
GX32	65	14	5	38	6	48	51	63	75	183
GX40	65	14	5	38	6	48	51	63	75	183

Schemat połączeń elektrycznych



Certyfikaty i zgodność

Zgodność

CSA C22.2 n° 14
IEC/EN/BS 60947-1
IEC/EN/BS 60947-3
IEC/EN/BS 60947-5-1
IEC/EN/BS 61058-1
UL60947-4-1

The characteristics described in this document are subject to updates or modifications at any time. The descriptions, technical and functional information, illustrations and instructions in this brochure are purely illustrative, and are consequently not contractually binding

Certyfikaty

	cULus
	EAC

Klasyfikacja ETIM

ETIM 8,0	EC001029 - Przełącznik, kompletny

The characteristics described in this document are subject to updates or modifications at any time. The descriptions, technical and functional information, illustrations and instructions in this brochure are purely illustrative, and are consequently not contractually binding