



#### General characteristics

|                          |                                  |
|--------------------------|----------------------------------|
| Colour                   | Black                            |
| Type of positions        | 0 - 1, key extraction in 0 and 1 |
| Material                 | Polyamide                        |
| IEC degree of protection | IP66, IP67 and IP69K             |

#### Mechanical features

|                  |        |          |
|------------------|--------|----------|
| Mechanical life  | cycles | 1000000  |
| Mounting adapter |        | LPXAU120 |
| Weight           | g      | 60       |


#### UL technical data

|                         |                              |
|-------------------------|------------------------------|
| UL degree of protection | Type1, 2, 3R, 4, 4X, 12, 12K |
|-------------------------|------------------------------|

#### Ambient conditions

|             |                       |     |    |     |
|-------------|-----------------------|-----|----|-----|
| Temperature | Operating temperature | min | °C | -25 |
|             |                       | max | °C | +70 |
|             | Storage temperature   | min | °C | -40 |
|             |                       | max | °C | +85 |

#### Dimensions



#### Certifications and compliance

|              |                     |
|--------------|---------------------|
| Compliance   | CSA C22.2 n° 14     |
|              | IEC/EN/BS 60947-1   |
|              | IEC/EN/BS 60947-5-1 |
|              | UL508               |
| Certificates | CCC                 |
|              | cULus               |

#### ETIM classification

ETIM 8.0

EC000222 -  
Front element for  
selector switch