LPFB1134

PUSHBUTTON ACTUATOR, SPRING RETURN, WITH SYMBOL Ø30MM PLATINUM SERIES FLAT METAL, FLUSH, STOP/RED



General characteristics

Colour			Red
Type of positions			Flush pushbutton
Material			Aluminium and zinc alloy
IEC degree of protection			IP66, IP67 and IP69K

Mechanical features

Operating force		kg-lb	<0.5Kg / 1.1lb
Mechanical life - spring return actuators		cycles	5000000
Fixing			Without mounting adapter
Mounting adapter			LPXAU120M

UL technical data

UL degree of protection			Type1, 2, 3R, 4, 4X, 12, 12K

Ambient conditions

Temperature				
	Operating temperature			
		min	°C	-25
		max	°C	+70
	Storage temperature			
		min	°C	-40
		max	°C	+85

Dimensions



Certifications and compliance

Compliance		
	CSA C22.2 n° 14	
	IEC/EN/BS 60947-1	
	IEC/EN/BS 60947-5-1	
	UL508	
Certificates		
	cULus	

ETIM classification

ETIM 8.0	EC000221 - Front element for push button

The characteristics described in this document are subject to updates or modifications at any time. The descriptions, technical and functional information, illustrations and instructions in this brochure are purely illustrative, and are consequently not contractually binding