



Electrical features

Relay adj range	A	32-38
-----------------	---	-------

IEC technical characteristics ($\leq 440V$)		
---	--	--

le	A	38
kW	kW	18.5

Components

Starter enclosure standard supplied	M25PA
-------------------------------------	-------

Contactor standard supplied	BF3800A
-----------------------------	---------

Thermal relay standard supplied	RF383800
---------------------------------	----------

UL technical data

Maximum UL/CSA horsepower ratings single-phase			
--	--	--	--

110V-120V	HP	3
220V-240V	HP	7.5

Maximum UL/CSA horsepower ratings three-phase, 3-pole			
---	--	--	--

200V-208V	HP	10
220V-240V	HP	15
440V-480V	HP	30
550V-600V	HP	30

UL degree of protection	Type 1, 12K, 4, 4X
-------------------------	--------------------

Mechanical features

Weight	g	2880
--------	---	------

Ambient conditions

Operating temperature			
-----------------------	--	--	--

min	°C	-25
max	°C	+60

Storage temperature			
---------------------	--	--	--

min	°C	-40
max	°C	+70

Resistance & Protection

Frontal IP degree	IP65
-------------------	------

ETIM classification

ETIM 8.0	EC001037 - Motor starter/Motor starter combination
----------	--