



General characteristics

Number of poles	Nr.	3
Overvoltage category		III
Pollution degree		3
Frontal IP degree		IP20
Type of release		Thermal
Protection fuse		
	gG (IEC)	A 6
	aM (IEC)	A 4
	RK5 (UL)	A 10
Phase failure detection		yes
Reset mode		Automatic

Power circuit characteristics

Rated insulation voltage U_i IEC/EN	V	690
Rated impulse withstand voltage U_{imp}	kV	8
Rated operational voltage	V	690
Operational frequency		
	min	Hz 0
	max	Hz 400
Operational current I_e		
	Operational current min	A 1.4
	Operational current max	A 2.3
Tripping class		10A
Test Button		Yes
Trip indicator		yes
Terminals		

type		screw and washer
screw		M4
width	mm	9.8
tool		Phillips 2

Tightening torque for terminals

min	Nm	2.3
max	Nm	2.3
min	lbin	1.7
max	lbin	1.7

Conductor section

AWG/kcmil max	10
---------------	----

Auxiliary circuit characteristics

Auxiliary contacts			
	NO	Nr.	1
	NC	Nr.	1
Auxiliary Rated insulation voltage Ui IEC/EN		V	690
Auxiliary Rated impulse withstand voltage Uimp		kV	6
Auxiliary Rated operational voltage		V	690

Operating current AC15

24V	A	1.5
120V	A	1.5
240V	A	0.75

IEC Conventional free air thermal current $I_{th} \leq 40^{\circ}\text{C}$

A	10
---	----

Terminals

Auxiliary circuit type		screw and washer
Auxiliary circuit screw		M3,5
Auxiliary circuit width	mm	8
Auxiliary circuit tool		Phillips 1

Conductor section

Auxiliary circuit Flexible w/o lug max	mm ²	2.5
Auxiliary circuit Flexible c/w lug max	mm ²	2.5

Tightening torque for terminals

Auxiliary circuit min	Nm	1
Auxiliary circuit max	Nm	1
Auxiliary circuit min	lbin	0.74
Auxiliary circuit max	lbin	0.74

UL/CSA and IEC/EN 60947-5-1 designation

C300-R300

Ambient conditions

Operating temperature

min	°C	-20
max	°C	55

Storage temperature

min	°C	-55
max	°C	70

Compensation temperature

min	°C	-15
max	°C	55

Max altitude

m	3000
---	------

Mechanical features

Operating position

normal allowable	Vertical plan $\pm 30^{\circ}$
	Direct mounting on BG06... BG09... BG12...

Fixing

Weight


g	116
---	-----

UL technical data


Full-load current (FLA) for three-phase AC motor

at 480V	A	2.3
at 600V	A	2.3

Dimensions



Wiring diagrams



Certifications and compliance

Compliance

CSA C22.2 n° 14

IEC/EN 60947-1

IEC/EN 60947-4-1

UL508

Certifications

CCC

CSA

cULus

EAC

ETIM classification

ETIM 8.0

EC000106 -
Thermal overload
relay