



General characteristics

Description	Compact, 1 operating threshold
Residual operation characteristic	Type A
N° of operating threshold	1

Control circuit

Toroidal transformer	Incorporated diam. 60mm/2.36"
----------------------	-------------------------------

Adjustments

Tripping set-point ($I_{\Delta n}$)

(x0.1)	A	0.025...0.25
(x1)	A	0.25...2.5
(x10)	A	2.5...25

Tripping delay time

(tx1)	s	0.02...0.5
(tx10)	s	0.2...5

Selection of multiplier for $I_{\Delta n}$ and t	By dip switches
--	-----------------

Resetting	Configurable automatic or manual by button on front
-----------	---

Test Button	Yes
-------------	-----

Shunt circuit control	No
-----------------------	----

Auxiliary supply

Auxiliary rated supply voltage U_s	110...125VAC/DC; 220...240/380...415VAC
--------------------------------------	---

Operational limits	110...125VAC/DC or 220...240VAC or 380...415VAC
--------------------	---

Output contacts	1
-----------------	---

Rated frequency	Hz	50...60
-----------------	----	---------

Power consumption Max	VA	3
-----------------------	----	---

Relay outputs

Relay state	Normally de-energised
-------------	-----------------------

Contact arrangement	1 changeover SPDT (trip)
---------------------	--------------------------

Rated contact capacity IEC I_{th}	5A - 250VAC
-------------------------------------	-------------


Insulations

Power frequency withstand voltage	kV	2.5kV for 60s
-----------------------------------	----	---------------

Indications


Auxiliary voltage available (ON)	Green LED
----------------------------------	-----------

Relay tripping (TRIP)				Red LED		
Connections						
Terminals type				Fixed		
Tightening torque for terminals				max	Nm	0.5
				max	lbin	4.5
Conductor section		AWG/Kcmil		min		24
				max		12
		IEC		min	mm²	0.2
				max	mm²	2.5
Operations						
Mechanical life				cycles	50000000	
Electrical life				cycles	300000	
Ambient conditions						
Temperature		Operating temperature		min	°C	-10
				max	°C	+60
		Storage temperature		min	°C	-20
				max	°C	+80
Relative humidity				%	≤90%	
Housing						
Material				Self-extinguishing polycarbonate		
Mounting				35mm DIN rail		
Degree of protection				IP20 terminals		
Dimensions (W x H x D)				mm	100x110x70	
Weight				g	485	
Dimensions						



TYPE	A	B	C	D	E	F	G	H
RC35	100 (3.94")	110 (4.33")	70 (2.75")	35 (1.38")	47 (1.85")	60 (2.36")	60 (2.36")	50 (1.97")
RC60	100 (3.94")	110 (4.33")	70 (2.75")	60 (2.36")	47 (1.85")	60 (2.36")	60 (2.36")	50 (1.97")
RC80	150 (5.90")	160 (6.30")	70 (2.75")	80 (3.15")	70 (2.75")	110 (4.33")	60 (2.36")	50 (1.97")
RC110	150 (5.90")	160 (6.30")	70 (2.75")	110 (4.33")	70 (2.75")	110 (4.33")	60 (2.36")	50 (1.97")

Wiring diagrams



Certifications and compliance

Compliant with standards

IEC/EN 60947-2

Certificates

EAC

ETIM classification

ETIM 8.0

EC001445 -
Residual current
monitoring relay