BF330T4E110

FOUR-POLE CONTACTOR, IEC OPERATING CURRENT ITH (AC1) = 500A, AC/DC COIL, 60… 130VAC/DC



Contact characteristics			
Number of poles		Nr.	4
Rated insulation voltage Ui IEC/EN		V	1000
Rated impulse withstand voltage Uimp		kV	8
Operational frequency			
	min	Hz	25
	max	Hz	400
IEC Conventional free air thermal current Ith ≤ 40°C		A	500
Operational current Ie			
	AC-1 (≤40°C)	A	500
	AC-1 (≤55°C)	A	415
	AC-1 (≤70°C)	A	360
	AC-3 (≤440V ≤55°C)	A	330
	AC-4 (400V)	A	160
Rated operational power AC-3 (T≤55°C)			
	230V	kW	90
	400V	kW	160
	415V	kW	160
	440V	kW	160
	500V	kW	200
	690V	kW	250
	1000V	kW	185
Rated operational current AC-3 (T≤55°C)			
	230V	A	330
	400V	A	330
	415V	A	330
	440V	A	330
	500V	A	300
	690V	A	300
	1000V	A	140
Rated operational power AC-1 (T≤40°C)			
	230V	kW	189
	400V	kW	329
	500V	kW	362
	690V	kW	568
IEC max current Ie in DC1 with L/R ≤ 1ms with 1 poles in series			
	75V	A	375
	110V	A	195
IEC max current Ie in DC1 with L/R ≤ 1ms with 2 poles in series			
	75V	A	375
	110V	A	350
	220V	A	300
IEC max current Ie in DC1 with L/R ≤ 1ms with 3 poles in series			
	75V	A	375
	110V	A	350

The characteristics described in this document are subject to updates or modifications at any time. The descriptions, technical and functional information, illustrations and instructions in this brochure are purely illustrative, and are consequently not contractually binding

	220V	A	350
	330V	A	300
IEC max current Ie in DC1 with L/R ≤ 1ms with 4 poles in series			
	75V	A	375
	110V	A	350
	220V	A	350
IEC max current Ie in DC3-DC5 with L/R ≤ 15ms with 1 poles in series			
	75V	A	310
	110V	A	170
IEC max current Ie in DC3-DC5 with L/R ≤ 15ms with 2 poles in series			
	75V	A	310
	110V	A	290
	220V	A	230
IEC max current Ie in DC3-DC5 with L/R ≤ 15ms with 3 poles in series			
	75V	A	310
	110V	A	310
	220V	A	290
	330V	A	230
IEC max current Ie in DC3-DC5 with L/R ≤ 15ms with 4 poles in series			
	75V	A	310
	110V	A	310
	220V	A	310
	330V	A	310
	460V	A	230
Short-time allowable current for 10s (IEC/EN60947-1)		A	2640
Protection fuse			
	gG (IEC)	A	630
	aM (IEC)	A	500
Making capacity (RMS value)		A	3300
Breaking capacity at voltage			
	440V	A	2640
	500V	A	2240
	690V	A	2000
Resistance per pole (average value)		mΩ	0.12
Power dissipation per pole (average value)			
	Ith	W	30
	AC-3	W	13
Tightening torque for terminals			
	min	Nm	35
	max	Nm	35
	min	lbin	310
	max	lbin	310
Tightening torque for coil terminal			
	min	Nm	0.8
	max	Nm	1
Power terminal protection according to IEC/EN 60529			IP00
Mechanical features			
Operating position			
	normal		Vertical plan
	allowable		±30°
Fixing			Screw
Operations			
Mechanical life		cycles	5000000

The characteristics described in this document are subject to updates or modifications at any time. The descriptions, technical and functional information, illustrations and instructions in this brochure are purely illustrative, and are consequently not contractually binding

Electrical life			cycles	700000
Safety related data				
Performance level B10d according to EN/ISO 13489-1				
		rated load	cycles	700000
		mechanical load	cycles	5000000
EMC compatibility				yes
AC coil operating				
Rated AC voltage at 50/60Hz, 60Hz				
		min	V	60
		max	V	130
AC operating voltage				
	of 50/60Hz coil powered at 50Hz			
	pick-up			
		min	%Us	80 Us min
		max	%Us	110 Us max
	drop-out			
		max	%Us	≤70 Us min
	of 50/60Hz coil powered at 60Hz			
	pick-up			
		min	%Us	80 Us min
		max	%Us	110 Us max
	drop-out			
		max	%Us	≤70 Us min
AC average coil consumption at 20°C				
	of 50/60Hz coil powered at 50Hz			
		in-rush	VA	300
		holding	VA	6.4
	of 50/60Hz coil powered at 60Hz			
		in-rush	VA	300
		holding	VA	6.4
	of 60Hz coil powered at 60Hz			
		in-rush	VA	300
		holding	VA	6.4
Dissipation at holding ≤20°C 50Hz			W	3.5…8.0
DC coil operating				
DC rated control voltage				
		min	V	60
		max	V	130
max			V	130
DC operating voltage				
	pick-up			
		min	%Us	85 Us min
		max	%Us	110 Us max
	drop-out			
		max	%Us	≤70 Us min
Average coil consumption ≤20°C				
		in-rush	W	220
		holding	W	2.7
Max cycles frequency				
Mechanical operation			cycles/h	1000
Operating times				
Average time for Us control				
	in AC			


The characteristics described in this document are subject to updates or modifications at any time. The descriptions, technical and functional information, illustrations and instructions in this brochure are purely illustrative, and are consequently not contractually binding

	Closing NO			
		min	ms	80
		max	ms	120
	Opening NO			
		min	ms	30
		max	ms	75
UL technical data				
Rated operational voltage AC (UL)			V	600
Yielded mechanical performance				
	for three-phase AC motor			
		200/208V	HP	100
		220/240V	HP	125
		460/480V	HP	250
		575/600V	HP	300
General USE				
	Contactor			
		AC current	A	500
Short-circuit protection fuse, 600V				
	High fault			
		Short circuit current	kA	100
		Fuse rating	A	600
		Fuse class		J
	Standard fault			
		Short circuit current	kA	18
		Fuse rating	A	600
		Fuse class		RK5
Ambient conditions				
Temperature				
	Operating temperature			
		min	°C	-40
		max	°C	70
	Storage temperature			
		min	°C	-50
		max	°C	80
Max altitude			m	3000
Resistance & Protection				
Pollution degree				3
Dimensions				


The characteristics described in this document are subject to updates or modifications at any time. The descriptions, technical and functional information, illustrations and instructions in this brochure are purely illustrative, and are consequently not contractually binding

BF330T4E110

FOUR-POLE CONTACTOR, IEC OPERATING CURRENT ITH (AC1) = 500A, AC/DC COIL, 60… 130VAC/DC



Wiring diagrams



Certifications and compliance

Compliance

CSA C22.2 n° 60947-1
CSA C22.2 n° 60947-4-1
IEC/EN/BS 60947-1
IEC/EN/BS 60947-4-1
UL 60947-1
UL 60947-4-1

Certificates

cULus

ETIM classification

ETIM 8.0	EC000066 - Power contactor, AC switching

The characteristics described in this document are subject to updates or modifications at any time. The descriptions, technical and functional information, illustrations and instructions in this brochure are purely illustrative, and are consequently not contractually binding