



Contact characteristics

Number of poles	Nr.	3
Rated insulation voltage U_i IEC/EN	V	1000
Rated impulse withstand voltage U_{imp}	kV	8
Operational frequency		
	min	Hz 25
	max	Hz 400
IEC Conventional free air thermal current $I_{th} \leq 40^\circ\text{C}$	A	115
Operational current I_e		
	AC-1 ($\leq 55^\circ\text{C}$)	A 130
IEC max current I_e in DC1 with $L/R \leq 1\text{ms}$ with 3 poles in series		
	400V	A 100
	600V	A 80
	800V	A 65
	1000V	A 60
Short-time allowable current for 10s (IEC/EN60947-1)	A	640
Protection fuse		
	gG (IEC)	A 125
	aM (IEC)	A 80
Resistance per pole (average value)	m Ω	0.6
Power dissipation per pole (average value)		
	I_{th}	W 7.9
Tightening torque for terminals		
	min	Nm 4
	max	Nm 5
	min	lbin 2.95
	max	lbin 3.69
Tightening torque for coil terminal		
	min	Nm 0.8
	max	Nm 1
	min	lbin 0.8
	max	lbin 0.74
Max number of wires simultaneously connectable	Nr.	2
Conductor section		
AWG/Kcmil		
	max	2
Flexible w/o lug conductor section		
	min	mm ² 1.5
	max	mm ² 35
Flexible c/w lug conductor section		
	min	mm ² 1.5
	max	mm ² 35
Power terminal protection according to IEC/EN 60529		IP20 front

Mechanical features

Operating position


	normal allowable	Vertical plan ±30°		
Fixing		Screw / DIN rail 35mm		
Weight	g	1240		
Operations				
Mechanical life	cycles	15000000		
Safety related data				
Performance level B10d according to EN/ISO 13489-1				
	mechanical load	cycles	15000000	
EMC compatibility		yes		
AC coil operating				
Rated AC voltage at 60Hz	V	575		
AC operating voltage				
of 60Hz coil powered at 60Hz				
pick-up				
	min	%Us	80	
	max	%Us	110	
drop-out				
	min	%Us	20	
	max	%Us	55	
AC average coil consumption at 20°C				
of 60Hz coil powered at 60Hz				
	in-rush	VA	210	
	holding	VA	15	
Dissipation at holding ≤20°C 50Hz	W	5		
Max cycles frequency				
Mechanical operation	cycles/h	3600		
Operating times				
Average time for Us control				
in AC				
Closing NO				
	min	ms	12	
	max	ms	28	
Opening NO				
	min	ms	8	
	max	ms	22	
in DC				
Closing NO				
	min	ms	40	
	max	ms	85	
Opening NO				
	min	ms	20	
	max	ms	55	
UL technical data				
Rated operational voltage AC (UL)	V	600		
General USE				
Contactor				
	AC current	A	115	
4 poles in series DC1				
	600V	A	100	
Ambient conditions				
Temperature				
Operating temperature				

Storage temperature	min	°C	-50
	max	°C	70
Max altitude	min	°C	-60
	max	°C	80
		m	3000



Resistance & Protection

Pollution degree 3

Dimensions



Wiring diagrams



Certifications and compliance

Compliance

CSA C22.2 n° 60947-1

CSA C22.2 n° 60947-4-1

IEC/EN/BS 60947-1

IEC/EN/BS 60947-4-1

UL 60947-1

UL 60947-4-1

ETIM classification

ETIM 8.0

EC002552 -
Power contactor,
DC switching