



Contact characteristics

Number of poles	Nr.	3
Rated insulation voltage U_i IEC/EN	V	690
Rated impulse withstand voltage U_{imp}	kV	8
Operational frequency	min	Hz 25
	max	Hz 400
IEC Conventional free air thermal current $I_{th} \leq 40^\circ\text{C}$	A	160
Rated operational power AC-6b ($T \leq 40^\circ\text{C}$)	230V	kvar 45
	400V	kvar 75
	440...480V	kvar 85
	690V	kvar 135
Short-time allowable current for 10s (IEC/EN60947-1)	A	920
Protection fuse	gG (IEC)	A 160
Making capacity (RMS value)	A	1500
Breaking capacity at voltage	440V	A 1200
	500V	A 850
	690V	A 905
Resistance per pole (average value)	m Ω	0.45
Power dissipation per pole (average value)	I_{th}	W 11.5
Tightening torque for terminals	min	Nm 6
	max	Nm 7
	min	lbin 4.4
	max	lbin 5.2
Tightening torque for coil terminal	min	Nm 0.8
	max	Nm 1
	min	lbin 0.59
	max	lbin 0.74
Max number of wires simultaneously connectable	Nr.	2
Conductor section	AWG/Kcmil	
	max	2/0
Flexible w/o lug conductor section	min	mm ² 1.5
	max	mm ² 70
Flexible c/w lug conductor section	min	mm ² 1.5
	max	mm ² 70
Power terminal protection according to IEC/EN 60529		IP20 front

Mechanical features

Operating position

	normal allowable	Vertical plan ±30°
Fixing		Screw / DIN rail 35mm
Weight	g	2095

Operations

Mechanical life	cycles	15000000
Electrical life	cycles	1200000

Safety related data

Performance level B10d according to EN/ISO 13489-1

	rated load mechanical load	cycles	1200000
		cycles	15000000
EMC compatibility			yes

AC coil operating

Rated AC voltage at 60Hz	V	460
--------------------------	---	-----

AC operating voltage

of 60Hz coil powered at 60Hz

pick-up

min	%Us	80
max	%Us	110

drop-out

min	%Us	20
max	%Us	55

Max cycles frequency

Mechanical operation	cycles/h	1500
----------------------	----------	------

Operating times

Average time for Us control

in AC

Closing NO

min	ms	16
max	ms	32

Opening NO

min	ms	9
max	ms	24

UL technical data

Rated operational voltage AC (UL)	V	600
-----------------------------------	---	-----

General USE

Contactor

AC current	A	160
------------	---	-----

Ambient conditions

Temperature

Operating temperature

min	°C	-50
max	°C	70

Storage temperature


min	°C	-60
max	°C	80

Max altitude	m	3000
--------------	---	------


Resistance & Protection

Pollution degree	3
------------------	---

Dimensions



Wiring diagrams



Certifications and compliance

Compliance

CSA C22.2 n° 60947-1

CSA C22.2 n° 60947-4-1

IEC/EN/BS 60947-1

IEC/EN/BS 60947-4-1

UL 60947-1

UL 60947-4-1

Certificates

CCC

cULus

ETIM classification

ETIM 8.0

EC001079 -
Capacitor
contactor