



Contact characteristics

Number of poles		Nr.	2	
Rated insulation voltage Ui IEC/EN		V	690	
Rated impulse withstand voltage Uimp		kV	6	
IEC Conventional free air thermal current Ith ≤ 40°C		A	10	
Tightening torque for terminals		min	Nm	0.8
		max	Nm	1
		min	lbin	7
		max	lbin	9
Max number of wires simultaneously connectable		Nr.	2	
Conductor section				
AWG/Kcmil				
		max	14	
Flexible w/o lug conductor section		min	mm²	0.75
		max	mm²	2.5
Flexible c/w lug conductor section		min	mm²	0.75
		max	mm²	2.5
Flexible with insulated spade lug conductor section		min	mm²	0.75
		max	mm²	2.5


Mechanical features

Operating position	normal allowable	On vertical plane Any
Fixing		Side mounting
Weight	g	44
Terminals screw		Screw

Auxiliary contact characteristics

Type of contact			2NO
Thermal current Ith	A		10
IEC/EN 60947-5-1 designation	A600 - Q600		
Operating current AC15	230V	A	3
	400V	A	1.9
	500V	A	1.4
Operating current DC13	24V	A	3
	48V	A	1.5
	60V	A	1.2
	110V	A	0.6
	125V	A	0.55
	220V	A	0.27

	600V	A	0.1
Electrical characteristics			
Conductivity			5V 10 mA
UL/CSA and IEC/EN 60947-5-1 designation			A600 Q600
Operating current AC15			
	120V	A	6
	240V	A	3
	480V	A	1.5
	600V	A	1.2
Operating current DC13			
	12V	A	10
	250V	A	0.27
	440V	A	0.15
	500V	A	0.13
UL technical data			
Rated operational voltage AC (UL)		V	600
Ambient conditions			
Temperature			
Operating temperature			
	min	°C	-50
	max	°C	+70
Storage temperature			
	min	°C	-60
	max	°C	+80
Max altitude		m	3000
Dimensions			



Wiring diagrams

Certifications and compliance

Certificates

CCC
cULus