



Product designation

Product type designation

Auxiliary supply U_s

Operational frequency

min	Hz	50
max	Hz	60

Current inputs

Primary current I_{pn} (/5)	A	150
-------------------------------	---	-----

Secondary output current	A	5
--------------------------	---	---

Overload withstand I_{pn}	%	120
-----------------------------	---	-----

Insulations

Rated insulation voltage U_i IEC/EN	V	720
---------------------------------------	---	-----

IEC rated short-time thermal current I_{th}	I_{th} for s	40...60
---	----------------	---------

IEC rated dynamic current I_{dyn}	I_{th} for s	2.5
-------------------------------------	----------------	-----

Insulation dry type	Class E
---------------------	---------

Mechanical features

Terminals type	Screw
----------------	-------

Fixing	Screw fixing
--------	--------------

Ambient conditions

Temperature

Operating temperature

min	°C	-25
max	°C	+50


Storage temperature

min	°C	-40
max	°C	+80

Relative humidity	%	90
-------------------	---	----

Protection degree	IP30
-------------------	------

Dimensions



Certifications and compliance

Compliance

IEC/EN/BS 61869-1

IEC/EN/BS 61869-2

Certificates

EAC

ETIM classification

ETIM 8.0

EC002048 -
Current
transformer