



Current
trasformers KIT -
3
DM1TP0100FKIT
with UTF
certificate
DM1TP0100FKIT

Product designation

Product type designation

Auxiliary supply U_s

Operational frequency

min	Hz	50
max	Hz	60

Current inputs

Primary current I_{pn} (/5)	A	100
-------------------------------	---	-----

Secondary output current	A	5
--------------------------	---	---

Overload withstand I_{pn}	%	120
-----------------------------	---	-----

Burden

cl. 0.5s	VA	2.5
cl. 0.5	VA	3.75

Insulations

Rated insulation voltage U_i IEC/EN	V	720
---------------------------------------	---	-----

IEC rated short-time thermal current I_{th}	I_{th} for s	40...60
---	----------------	---------

IEC rated dynamic current I_{dyn}	I_{th} for s	2.5
-------------------------------------	----------------	-----

Insulation dry type	Class E
---------------------	---------

Mechanical features

Terminals type	Screw
----------------	-------

Fixing	DIN rail or by Screw
--------	-------------------------

Weight	g	480
--------	---	-----

Ambient conditions

Temperature

Operating temperature

min	°C	-25
max	°C	+50

Storage temperature

min	°C	-40
max	°C	+80

Relative humidity	%	90
-------------------	---	----

Protection degree	IP30
-------------------	------

Certifications and compliance

Compliance

IEC/EN 61869-1

IEC/EN 61869-2

ETIM classification

ETIM 8.0

EC002048 -
Current
transformer