



Contact characteristics

IEC Conventional free air thermal current $I_{th} \leq 40^{\circ}\text{C}$	A	16
Rated insulation voltage U_i IEC/EN	V	1000
Rated impulse withstand voltage U_{imp}	kV	8
Operating current I_e		
AC21A		
	400V	A 16
	500V	A 16
	690V	A 16
AC22A		
	400V	A 16
	500V	A 16
	690V	A 16
AC23A		
	400V	A 16
	500V	A 16
	690V	A 16
Power dissipation per pole max	W	0.2
Rated operational power AC23A		
	400V	kW 7.5
	690V	kW 11
Reactive power for control of capacitors at		
Conditional short-circuit current (rms)	kA	10
Short-circuit protection with fuse	Class/A	gG16
Making capacity AC23A 400V	A	160
Breaking capacity AC23A 400V	A	128
Mechanical life	cycles	100000
Electrical life AC21A	cycles	100000

Mechanical features

Operating position	normal allowable	Vertical plan Any
Terminals	type	Pillar
	width	mm 5.6
	height	mm 6.5
	screw	M4
	tool	Phillips 2
Tightening torque for terminals	min	Nm 1.8
	max	Nm 2
	min	lbin 16
	max	lbin 18
Conductor section	IEC min	mm ² 0.75

IEC/EN TYPE IP65 PLASTIC ENCLOSURE SWITCH DISCONNECTOR, FOUR-POLE. WITH ROTATING RED/YELLOW HANDLE, 16A. ENCLOSURE DIMENSIONS: 100X168X97MM/3.9X6.6X3.8"

IEC max	mm ²	16
AWG/kcmil min		18
AWG/kcmil max	kcmil	6

Ambient conditions

Operating temperature

min	°C	-25
max	°C	+55

Storage temperature

min	°C	-40
max	°C	+70

Max altitude

m 3000

Resistance & Protection

Frontal IP degree

IP65


IP degree of protection

IP65


Pollution degree

3

Dimensions



Wiring diagrams



Certifications and compliance

Compliance

IEC/EN 60947-1
IEC/EN 60947-3

Certifications

EAC

ETIM classification

ETIM 8.0

EC000216 -
Switch
disconnector