



Contact characteristics

IEC Conventional free air thermal current $I_{th} \leq 40^{\circ}\text{C}$	A	200
Rated insulation voltage U_i IEC/EN	V	800
Rated impulse withstand voltage U_{imp}	kV	8
Operating current I_e		
AC21A		
	400V	A 200
	500V	A 200
	690V	A 200
AC22A		
	400V	A 200
	500V	A 200
	690V	A 200
AC23A		
	400V	A 200
	500V	A 200
	690V	A 160
Power dissipation per pole max	W	13
Rated operational power AC23A		
	400V	kW 110
	690V	kW 132
Reactive power for control of capacitors at		
Conditional short-circuit current (rms)	kA	100
Specific let through energy I^2t	kA ² s	0.478
Making capacity AC23A 400V	A	2000
Breaking capacity AC23A 400V	A	1600
Mechanical life	cycles	10000
Electrical life AC21A	cycles	1000 (AC23A 400V)


Mechanical features

Operating position	normal allowable	Vertical plan Any
Fixing		Screw
Terminals	type screw	Bar M8
Tightening torque for terminals	max	Nm 13
	max	lbin 10
Conductor section		
Bar dimensions max		25x3

Ambient conditions

Operating temperature	min	$^{\circ}\text{C}$	-25
-----------------------	-----	--------------------	-----

	max	°C	55
Storage temperature	min	°C	-40
	max	°C	70
Max altitude	m		3000
Resistance & Protection			
Frontal IP degree			IP20
Pollution degree			3
Dimensions			




Wiring diagrams

Four-pole disconnectors with fuse holders

GE0050 FT4 - GE0125 FT4

GE0160 NT4 - GE0800 NT4

GE0160 BT4 - GE0800 BT4



Certifications and compliance

Compliance

IEC/EN 60947-1

IEC/EN 60947-3

Certifications

EAC

ETIM classification

ETIM 8.0

EC000216 -
Switch
disconnecter