



Contact characteristics

IEC Conventional free air thermal current $I_{th} \leq 40^\circ\text{C}$	A	800
Rated insulation voltage U_i IEC/EN	V	1000
Rated impulse withstand voltage U_{imp}	kV	12
Operating current I_e		
AC21A		
	400V	A 800
	500V	A 800
	690V	A 630
AC22A		
	400V	A 800
	500V	A 800
	690V	A 630
AC23A		
	400V	A 630
	500V	A 630
	690V	A 400
Power dissipation per pole max	W	63
Rated operational power AC23A		
	400V	kW 355
	690V	kW 370
Reactive power for control of capacitors at		
Conditional short-circuit current (rms)	kA	100
Specific let through energy I^2t	kA ² s	4.6
Making capacity AC23A 400V	A	6300
Breaking capacity AC23A 400V	A	5100
Mechanical life	cycles	5000
Electrical life AC21A	cycles	500 (AC23A 400V)

Mechanical features

Operating position	normal allowable	Vertical plan Any
Fixing		Screw
Terminals	type screw	Bar 4x M8
Tightening torque for terminals	max	Nm 13
	max	lbin 10
Conductor section		
Bar dimensions max		50x6
Ambient conditions		
Operating temperature	min	$^\circ\text{C}$ -25

	max	°C	55
Storage temperature	min	°C	-40
	max	°C	70
Max altitude	m		3000

Resistance & Protection

Frontal IP degree	IP20
-------------------	------

Pollution degree	3
------------------	---

Dimensions


Wiring diagrams

Four-pole disconnectors with fuse holders

GE0050 FT4 - GE0125 FT4

GE0160 NT4 - GE0800 NT4

GE0160 BT4 - GE0800 BT4



Certifications and compliance

Compliance	IEC/EN 60947-1
	IEC/EN 60947-3

Certifications	EAC
----------------	-----

ETIM classification

ETIM 8.0	EC000216 - Switch disconnecter
----------	--------------------------------------