# GF1053U

ROTARY CAM SWITCH GF SERIES, CHANGEOVER SWITCH 3 POLES 10A, FOR FRONT MOUNTING WITH BLACK HANDLE, FRONT PLATE 30X30MM

## General characteristics

| | | | |
|---|---|---|---|
| Switching diagram | | | 53 - Changeover switch 3 poles - 2 speed motor starting with separate windings |
| N° of elements | | | 3 |
| Mounting form | | | U - Front mounting with black handle |

## Contact characteristics

| | | | |
|---|---|---|---|
| Rated insulation voltage Ui | | | |
| | IEC/EN | V | 480 |
| | UL/CSA | V | 240 |
| Rated impulse withstand voltage Uimp | | kV | 4 |
| Conventional free air thermal current Ith | | | |
| | IEC/EN | A | 10 |
| | UL/CSA | A | 10 |
| Rated operational voltage | | V | 480 |
| Rated operational impulse voltage | | kV | 4 |
| Maximum fuse size for short-circuit protection In (gG) | | | |
| | 10kA | A | 16 |
| Rated short time current Icw | | | |
| | 1s | kA | 250 |
| Conductivity | | | 10/5 mA/V |
| Operational current Ie IEC/EN | | | |
| AC1/AC21A | | | |
| | | A | 10 |
| AC15 | | | |
| | 110V | A | 5 |
| | 220/230V | A | 3 |
| | 380/400V | A | 2 |
| Rated operational power in AC | | | |
| Three-phase AC-3 | | | |
| | 220/230V | kW | 1.5 |
| | 380/440V | kW | 2.2 |
| Single-phase AC-3 | | | |
| | 110V | kW | 0.3 |
| | 220/230V | kW | 0.55 |
| | 380/440V | kW | 0.75 |
| Three-phase AC23A | | | |
| | 220/230V | kW | 1.8 |
| | 380/440V | kW | 3 |
| Single-phase AC23A | | | |
| | 110V | kW | 0.7 |
| | 220/230V | kW | 0.75 |
| | 380/440V | kW | 1.1 |
| Rated operational current in DC | | | |
| DC21A | | | |
| | 48V | A | 10 |
| | 60V | A | 7 |
| | 110V | A | 2 |
| | 220V | A | 0.7 |



The characteristics described in this document are subject to updates or modifications at any time. The descriptions, technical and functional information, illustrations and instructions in this brochure are purely illustrative, and are consequently not contractually binding

| | | | | |
|---|---|---|---|---|
| | | 440V | A | 0.2 |
| | DC13 | | | |
| | | 24V | A | 3 |
| | | 48V | A | 3 |
| | | 60V | A | 2 |
| | | 110V | A | 1 |
| | | 220V | A | 0.3 |
| | | 440V | A | 0.1 |
| Power dissipation | | | W | 0.4 |
| **Mechanical features** | | | | |
| Terminals screw | | | | 2.5M |
| Tightening torque for terminals max | | | Nm | 0.4 |
| Conductor size | | | | |
| | AWG - Rigid cable | | | |
| | | min | AWG | 20 |
| | | Max | AWG | 14 |
| | AWG - Flexible cable | | | |
| | | min | AWG | 20 |
| | | Max | AWG | 14 |
| | Conductor size (IEC) - Flexible cable | | | |
| | | min | mm² | 0.5 |
| | | Max | mm² | 1.5 |
| | Conductor size (IEC) - Rigid cable | | | |
| | | min | mm² | 0.5 |
| | | Max | mm² | 1.5 |
| Mechanical life | | | cycles | $1x10^6$ |
| **UL technical data** | | | | |
| Motor power for direct-on-line control | | | | |
| | for three-phase motor | | | |
| | | 240V | HP | 2 |
| | for single-phase motor | | | |
| | | 240V | HP | 0.75 |
| **Ambient conditions** | | | | |
| Temperature | | | | |
| | Operating temperature | | | |
| | | min | °C | -25 |
| | | max | °C | +55 |
| | Storage temperature | | | |
| | | min | °C | -40 |
| | | max | °C | +70 |
| **Resistance & Protection** | | | | |
| Frontal IP degree | | | | IP40 |
| Terminals IP degree | | | | IP20 |
| **Dimensions** | | | | |


The characteristics described in this document are subject to updates or modifications at any time. The descriptions, technical and functional information, illustrations and instructions in this brochure are purely illustrative, and are consequently not contractually binding


# GF1053U

ROTARY CAM SWITCH GF SERIES, CHANGEOVER SWITCH 3 POLES 10A, FOR FRONT MOUNTING WITH BLACK HANDLE, FRONT PLATE 30X30MM




| Series | Dimensions | | | | | | | | L Number of elements | | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | □A | C | D | ØD1 | ØD2 | E | □K | N | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 10 | 11 | 12 |
| **GF10** | 30 | 24 | 29 | 9 | 3.2 | 18.5 | – | Ø5 | 40 | 52 | 64 | 76 | 88 | 100 | 112 | 124 | – | – | – | – |
| **GF20** | 48 | 39.5 | 36 | 12 | 5 | 26.5 | 36 | □6 | 44 | 57.5 | 71 | 84.5 | 98 | 111.5 | 125 | 138.5 | 152 | 165.5 | 179 | 192.5 |

## Wiring diagrams




## Certifications and compliance

Compliance

| |
|---|
| CSA C22.2 n° 14 |
| IEC/EN/BS 60947-1 |
| IEC/EN/BS 60947-3 |
| IEC/EN/BS 60947-5-1 |
| UL60947-4-1 |

Certificates

| |
|---|
| cULus |
| EAC |

## ETIM classification

| | |
|---|---|
| ETIM 8.0 | EC001029 - Selector switch, complete |


The characteristics described in this document are subject to updates or modifications at any time. The descriptions, technical and functional information, illustrations and instructions in this brochure are purely illustrative, and are consequently not contractually binding