GF1085U

ROTARY CAM SWITCH GF SERIES, MULTI-STEP 1-2-3-4-5-6, 1 POLE 10A, FOR FRONT MOUNTING WITH BLACK HANDLE, FRONT PLATE 30X30MM

General characteristics

Switching diagram			85 - Multi-step 1-2-3-4-6 1 pole
N° of elements			3
Mounting form			U - Front mounting with black handle

Contact characteristics

Rated insulation voltage Ui			
	IEC/EN	V	480
	UL/CSA	V	240
Rated impulse withstand voltage Uimp		kV	4
Conventional free air thermal current Ith			
	IEC/EN	A	10
	UL/CSA	A	10
Rated operational voltage		V	480
Rated operational impulse voltage		kV	4
Maximum fuse size for short-circuit protection In (gG)			
	10kA	A	16
Rated short time current Icw			
	1s	kA	250
Conductivity			10/5 mA/V
Operational current Ie IEC/EN			
AC1/AC21A			
		A	10
AC15			
	110V	A	5
	220/230V	A	3
	380/400V	A	2
Rated operational power in AC			
Three-phase AC-3			
	220/230V	kW	1.5
	380/440V	kW	2.2
Single-phase AC-3			
	110V	kW	0.3
	220/230V	kW	0.55
	380/440V	kW	0.75
Three-phase AC23A			
	220/230V	kW	1.8
	380/440V	kW	3
Single-phase AC23A			
	110V	kW	0.7
	220/230V	kW	0.75
	380/440V	kW	1.1
Rated operational current in DC			
DC21A			
	48V	A	10
	60V	A	7
	110V	A	2
	220V	A	0.7
	440V	A	0.2
DC13			
	24V	A	3


The characteristics described in this document are subject to updates or modifications at any time. The descriptions, technical and functional information, illustrations and instructions in this brochure are purely illustrative, and are consequently not contractually binding


GF1085U


ROTARY CAM SWITCH GF SERIES, MULTI-STEP 1-2-3-4-5-6, 1 POLE 10A, FOR FRONT MOUNTING WITH BLACK HANDLE, FRONT PLATE 30X30MM


		48V	A	3
		60V	A	2
		110V	A	1
		220V	A	0.3
		440V	A	0.1
Power dissipation			W	0.4
Mechanical features				
Terminals screw				2.5M
Tightening torque for terminals max			Nm	0.4
Conductor size				
	AWG - Rigid cable			
		min	AWG	20
		Max	AWG	14
	AWG - Flexible cable			
		min	AWG	20
		Max	AWG	14
	Conductor size (IEC) - Flexible cable			
		min	mm²	0.5
		Max	mm²	1.5
	Conductor size (IEC) - Rigid cable			
		min	mm²	0.5
		Max	mm²	1.5
Mechanical life			cycles	1x10⁶
UL technical data				
Motor power for direct-on-line control				
	for three-phase motor			
		240V	HP	2
	for single-phase motor			
		240V	HP	0.75
Ambient conditions				
Temperature				
	Operating temperature			
		min	°C	-25
		max	°C	+55
	Storage temperature			
		min	°C	-40
		max	°C	+70
Resistance & Protection				
Frontal IP degree				IP40
Terminals IP degree				IP20

Dimensions









Drillings for 4 screws fixing (4V version).


Series	Dimensions								L Number of elements											
	□A	C	D	ØD1	ØD2	E	□K	N	1	2	3	4	5	6	7	8	9	10	11	12
GF10	30	24	29	9	3.2	18.5	–	Ø5	40	52	64	76	88	100	112	124	–	–	–	–
GF20	48	39.5	36	12	5	26.5	36	□6	44	57.5	71	84.5	98	111.5	125	138.5	152	165.5	179	192.5

Wiring diagrams

The characteristics described in this document are subject to updates or modifications at any time. The descriptions, technical and functional information, illustrations and instructions in this brochure are purely illustrative, and are consequently not contractually binding

GF1085U

ROTARY CAM SWITCH GF SERIES, MULTI-STEP 1-2-3-4-5-6, 1 POLE 10A, FOR FRONT MOUNTING WITH BLACK HANDLE, FRONT PLATE 30X30MM



Certifications and compliance

Compliance

CSA C22.2 n° 14
IEC/EN/BS 60947-1
IEC/EN/BS 60947-3
IEC/EN/BS 60947-5-1
UL60947-4-1

Certificates

cULus
EAC

ETIM classification

ETIM 8.0	EC001029 - Selector switch, complete

The characteristics described in this document are subject to updates or modifications at any time. The descriptions, technical and functional information, illustrations and instructions in this brochure are purely illustrative, and are consequently not contractually binding