



Contact characteristics

Contact configuration	1 C/O		
Rated insulation voltage U_i IEC/EN	V		250
Rated impulse withstand voltage U_{imp}	kV		4
IEC Conventional free air thermal current $I_{th} \leq 40^\circ\text{C}$	A		6
Maximum instantaneous current	A		20 (500ms)
Rated current (I_n)	A		6
UL/CSA and IEC/EN 60947-5-1 designation	B300 – R300		
Max contrrollable power in	AC-1	W	1500
	AC-15	VA	360
Rated operating power AC-1		VA	1500
Rated operating power AC-15	230 VAC	VA	360
Single-phase motor control	230VAC	kW	0.186
Rated operating current DC-1	30V	A	6
	110V	A	0.2
	220V	A	0.12
Minimum switching load	V / mA		5 / 100
Contact impedance	m Ω		100
Contact material	Ag/Ni		

Operating times

Closing	ms	≤ 8
Opening	ms	≤ 4

Operations

Mechanical life	cycles	10000000
Electrical life AC1	cycles	30000


Coil characteristics

Relay control voltage	V	220... 240VAC/VDC
Relay control voltage + socket	V	220...240VAC/DC
Average coil consumption AC at 20°C	VA	0.2
Average coil consumption DC at 20°C	W	0.2
Operating range	Closing	% U_n ≥ 75
	Opening	% U_n ≥ 5
Maximum cycle frequency	cycles/h	10000


Mechanical features

Max socket terminal tightening torque	Nm	0.5
Socket screw tightening tool (cross / flat blade)	PH0 / 3.5mm	
Conductor section	AWG/Kcmil	

		min	20	
		max	16	
IEC				
		min	mm ²	0.5
		max	mm ²	1.5
Operating position				
			normal	Any
Fixing				
			On 35mm DIN rail	
Ambient conditions				
Temperature				
Operating temperature				
		min	°C	-40
		max	°C	+70
Storage temperature				
		min	°C	-40
		max	°C	+80
Other features				
Indication				Yes (on the socket)
Mechanical contact position indicator				No
Mechanical test actuator				No
Dimensions				



Wiring diagrams



Certifications and compliance

Compliance

IEC/EN 61810

Certificates

cURus

EAC

VDE

ETIM classification

ETIM 8.0

EC001437 -
Switching relay