



General characteristics				
General characteristics				
Housing Material			Polymer thermoplastic	
Contact characteristics				
Type of contact	1NC (Key), 2NC+1NO (Solenoid)			
Thermal current I _{th}	A	10		
IEC/EN 60947-5-1 designation	A300 Q300			
Rated insulation voltage U _i	V	250		
Rated impulse withstand voltage U _{imp}	kV	2.5		
Short-circuit protection with fuse	Class/A	10 gG		
IEC Conventional free air thermal current I _{th} ≤ 40°C	A	10		
Operations				
Mechanical life	cycles	1000000		
B10d	cycles	4000000		
Mechanical operation	cycles/h	600		
Output characteristics				
Mechanical life	cycles	1000000		
Mechanical features				
Operating head fixing			Screwed	
Operating torque			15 (actuator insertion), 30 (Release actuator extraction), 1200 (locked actuator holding)	
Tightening torque (Max)			15 (actuator insertion), 30 (Release actuator extraction), 1200 (locked actuator holding)	
Switch fixing				
Contact terminals			Nm	2.5
			Nm	0.8
Body lid screw fixing			Nm	0.8
Conductor section				
IEC	min	mm ²	mm ²	1 or 2
				1.5
Cable connection				Self-releasing screw terminal
Cable entry				3 x M20
Weight			g	440
Ambient conditions				
Pollution degree				3

Temperature


Operating temperature

max °C +55


Storage temperature

min °C -40
max °C +70

Dimensions



Wiring diagrams



Certifications and compliance

Compliance

CSA C22.2 n°14
IEC/EN 60204
IEC/EN 60947-1
IEC/EN 60947-5-1
UL508
UNI EN ISO 14119

Certificates

cULus
EAC

ETIM classification

ETIM 8.0

EC000030 - End
switch