

**General characteristics**

Material

Housing

Polymer  
thermoplastic

**Contact characteristics**

Type of contact

1NO+1NC Snap  
action

Thermal current I<sub>th</sub>

A

10

IEC/EN 60947-5-1 designation

A600 Q600

Rated insulation voltage U<sub>i</sub>

V

690

Rated impulse withstand voltage U<sub>imp</sub>

kV

6

Insulation class

II

Short-circuit protection with fuse

Class/A

10 gG fuse

IEC Conventional free air thermal current I<sub>th</sub> ≤ 40°C

A

10

Resistance per pole (average value)

mΩ

<10

**Mechanical features**

Tightening torque (Max)

Contact terminals

Nm

1

lbin

0.74lbft

Cable connection

Self-releasing  
screw terminal

Cable entry

1 x M20

**Operations**

Mechanical life

cycles

>10000000

**Ambient conditions**

Temperature

Operating temperature

min

°C

-25

max

°C

+70

Storage temperature

min

°C

-40

max

°C

+70

**Resistance & Protection**

IP degree

Terminals

IP20


Body housing

IP54

Pollution degree

3

**Dimensions**



**Certifications and compliance**

Compliance

EN 60447.

IEC/EN 60204-1

IEC/EN 60947-1

IEC/EN 60947-5-1

Certificates

EAC

**ETIM classification**

ETIM 8.0

EC001258 - Foot switch