KNF4S11

LIMIT SWITCH, K SERIES, ADJUSTABLE ROLLER LEVER, 2 SIDE CABLE ENTRY. DIMENSIONS COMPATIBLE TO EN 50047, METAL BODY, CONTACTS 1NO+1NC SNAP ACTION. RUBBER ROLLER



General characteristics				
Material				
	Housing			Aluminium-zinc alloy
	Roller			Rubber
Contact characteristics				
Type of contact				1NO+1NC Snap action
Thermal current Ith			A	10
IEC/EN 60947-5-1 designation				A300 Q300
Rated insulation voltage Ui			V	440
Rated impulse withstand voltage Uimp			kV	4
Insulation class				II
Short-circuit protection with fuse			Class/A	10 gG/SC QUICK FUSE
Switching speed				
		min	m/s	0.5
		max	m/s	1.5
IEC Conventional free air thermal current Ith ≤ 40°C			A	10
Resistance per pole (average value)			mΩ	<10
Mechanical features				
Operating head fixing				Locking bayonet insert
Operating torque				
			Ncm	3
			ozin	4.25
Tightening torque (Max)				
	Switch fixing			
			Nm	2.5
			lbin	22.1
	Contact terminals			
			Nm	0.8
			lbin	7
	Body lid screw fixing			
			Nm	0.8
			lbin	7
Conductor section				
	AWG/Kcmil			
		min		16
		max		14
	IEC			
		min	mm²	1.5
		max	mm²	2.5
Cable connection				Self-releasing screw terminal
Cable entry				M20 on the sides

The characteristics described in this document are subject to updates or modifications at any time. The descriptions, technical and functional information, illustrations and instructions in this brochure are purely illustrative, and are consequently not contractually binding

Operations

Mechanical life		cycles	<10000000
Mechanical operation		cycles/h	3600

Ambient conditions

Temperature


Operating temperature			
	min	°C	-25
	max	°C	+70
Storage temperature			
	min	°C	-40
	max	°C	+70

Resistance & Protection

IP degree


Terminals		IP20
Body housing		IP65
Pollution degree		3

Dimensions



Wiring diagrams

The characteristics described in this document are subject to updates or modifications at any time. The descriptions, technical and functional information, illustrations and instructions in this brochure are purely illustrative, and are consequently not contractually binding



Certifications and compliance

Compliance

CSA C22.2 n° 14
EN 50047
IEC/EN 60204-1
IEC/EN 60947-1
IEC/EN 60947-5-1
UL508

Certificates

CCC
cULus
EAC

ETIM classification

ETIM 8.0	EC000030 - End switch

The characteristics described in this document are subject to updates or modifications at any time. The descriptions, technical and functional information, illustrations and instructions in this brochure are purely illustrative, and are consequently not contractually binding