# LPCB7355K21

KIT PLASTIC TRIPLE-TOUCH ACTUATOR, SPRING RETURN, 2 EXTERNAL FLUSH AND 1 MIDDLE EXTENDED PUSHBUTTONS. SPRING RETURN, ↑ STOP ↓ WITH MOUNTING ADAPTER AND 2 CONTACT ELEMENTS, 2NO+1NC. SCREW TERMINATION




| | | | |
|---|---|---|---|
| **General characteristics** | | | |
| Colour | | | Green/Red/Green |
| Type of positions | | | Triple-touch |
| IEC degree of protection | | | IP66, IP67 and IP69K |
| **Electrical characteristics** | | | |
| Rated insulation voltage Ui IEC/EN | | V | 690 |
| IEC Conventional free air thermal current Ith ≤ 40°C | | A | 10 |
| Conductivity | | | 1mA 5V |
| UL/CSA and IEC/EN 60947-5-1 designation | | | A600 Q600 |
| Operating current AC15 | | | |
| | 12V | A | 6 |
| | 24V | A | 6 |
| | 48V | A | 6 |
| | 120V | A | 6 |
| | 240V | A | 3 |
| | 400V | A | 1.9 |
| | 480V | A | 1.5 |
| | 500V | A | 1.4 |
| | 600V | A | 1.2 |
| Operating current DC13 | | | |
| | 12V | A | 3 |
| | 24V | A | 3 |
| | 48V | A | 1.5 |
| | 125V | A | 0.55 |
| | 250V | A | 0.27 |
| | 440V | A | 0.15 |
| | 500V | A | 0.13 |
| | 600V | A | 0.1 |
| Contact resistance | | mΩ | ≤20 |
| **Mechanical features** | | | |
| Operating force | | kg-lb | <0.5Kg / 1.1lb |
| Mechanical life | | cycles | 1000000 |
| Terminals screw | | | Screw |
| Conductor section | | | |
| IEC | | | |
| | max | mm² | 1 or 2 / 2.5 |
| Mounting adapter | | | LPXAU120 |
| **UL technical data** | | | |
| UL degree of protection | | | Type1, 2, 3R, 4, 4X, 12, 12K |
| **Ambient conditions** | | | |
| Temperature | | | |
| Operating temperature | | | |
| | min | °C | -25 |
| | max | °C | +70 |


The characteristics described in this document are subject to updates or modifications at any time. The descriptions, technical and functional information, illustrations and instructions in this brochure are purely illustrative, and are consequently not contractually binding

| | | | |
|---|---|---|---|
| Storage temperature | | | |
| | min | °C | -40 |
| | max | °C | +85 |

## Certifications and compliance

Compliance

- CSA C22.2 n° 14
- IEC/EN/BS 60947-1
- IEC/EN/BS 60947-5-1
- UL508

Certificates

- CCC
- cULus
- EAC
- RINA


The characteristics described in this document are subject to updates or modifications at any time. The descriptions, technical and functional information, illustrations and instructions in this brochure are purely illustrative, and are consequently not contractually binding