



General characteristics			
Colour			Green/Red
Type of positions			Double-touch with two flush pushbuttons
IEC degree of protection			IP66, IP67 and IP69K
Electrical characteristics			
Rated insulation voltage U_i IEC/EN	V		690
IEC Conventional free air thermal current $I_{th} \leq 40^\circ\text{C}$	A		10
Supply voltage (AC)	V		12...30
Supply voltage (DC)	V		12...30
Conductivity			1mA 5V
UL/CSA and IEC/EN 60947-5-1 designation			A600 Q600
Operating current AC15			
	12V	A	6
	24V	A	6
	48V	A	6
	120V	A	6
	240V	A	3
	400V	A	1.9
	480V	A	1.5
	500V	A	1.4
	600V	A	1.2
Operating current DC13			
	12V	A	3
	24V	A	3
	48V	A	1.5
	125V	A	0.55
	250V	A	0.27
	440V	A	0.15
	500V	A	0.13
	600V	A	0.1
Contact resistance		m Ω	≤ 20
Operations			
Electrical life		hours	100000
Mechanical features			
Operating force		kg-lb	<0.5Kg / 1.1lb
Mechanical life		cycles	1000000
Terminals screw			Screw
Conductor section			
	IEC		
		max	mm ² 1 or 2 / 2.5
Mounting adapter			L PXAU120
UL technical data			

KIT PLASTIC DOUBLE-TOUCH ACTUATOR, SPRING RETURN, WHITE INDICATOR, 2 FLUSH PUSHBUTTONS, GREEN RED/0 WITH MOUNTING ADAPTER AND 2 CONTACT ELEMENTS, 1NO+1NC. SCREW TERMINATION. LED INTEGRATED LAMP-HOLDER, STEADY LIGHT, 12...30VAC/DC

UL degree of protection

Type1, 2, 3R, 4,
4X, 12, 12K

Ambient conditions

Temperature

Operating temperature

min	°C	-25
max	°C	+70

Storage temperature

min	°C	-40
max	°C	+85

Certifications and compliance

Compliance

CSA C22.2 n° 14
IEC/EN/BS 60947-1
IEC/EN/BS 60947-5-1
UL508

Certificates

CCC
cULus
EAC
RINA