





General characteristics				
Colour			Green	
Type of positions			Monoblock pilot light	
Material			Polyamide	
IEC degree of protection			IP66, IP67 and IP69K on front; IP20 on rear	
Electrical characteristics				
Rated frequency		Hz	50-60	
Supply voltage (AC)		V	48 (-15% ... +10% Ue)	
Supply voltage (DC)		V	48 (-15% ... +10% Ue)	
Maximum current consumption		mA	≤ 20	
Operations				
Electrical life		hours	>30000	
Mechanical features				
Tightening torque for terminals max		Nm	0.8	
Terminals screw			Screw termination	
Conductor section		AWG/kcmil conductor section		
		min	18	
		max	16	
		IEC		
		max	mm²	2.5
Fixing			Ring fixing Ø22mm	
Weight			g	21
UL technical data				
UL degree of protection			Type1, 2, 3R, 4, 4X, 12, 12K on front	
Ambient conditions				
Temperature		Operating temperature		
		min	°C	-25
		max	°C	+70
Dimensions				



Wiring diagrams



Certifications and compliance

Compliance

CSA C22.2 n° 14

IEC/EN/BS 60947-1

IEC/EN/BS 60947-5-1

UL508

Certificates

cULus

EAC

ETIM classification

ETIM 8.0

EC000272 -
Indicator light
complete