



#### General characteristics

|                          |                                                                          |
|--------------------------|--------------------------------------------------------------------------|
| Colour                   | Red                                                                      |
| Type of positions        | Mushroom head pushbutton                                                 |
| Material                 | Aluminium and zinc alloy for metal parts and polyamide for plastic parts |
| IEC degree of protection | IP66, IP67 and IP69K                                                     |

#### Mechanical features

|                                   |        |                          |
|-----------------------------------|--------|--------------------------|
| Mechanical life - Latch actuators | cycles | 300000                   |
| Fixing                            |        | Without mounting adapter |
| Mounting adapter                  |        | LPXAU120M                |


#### UL technical data

|                         |                              |
|-------------------------|------------------------------|
| UL degree of protection | Type1, 2, 3R, 4, 4X, 12, 12K |
|-------------------------|------------------------------|

#### Ambient conditions

|             |                       |     |    |     |
|-------------|-----------------------|-----|----|-----|
| Temperature | Operating temperature | min | °C | -25 |
|             |                       | max | °C | +70 |
|             | Storage temperature   | min | °C | -40 |
|             |                       | max | °C | +85 |

#### Dimensions



Turn key to release

#### Certifications and compliance

|              |                     |
|--------------|---------------------|
| Compliance   | CSA C22.2 n° 14     |
|              | IEC/EN/BS 60947-1   |
|              | IEC/EN/BS 60947-5-1 |
|              | UL508               |
| Certificates | cULus               |

#### ETIM classification

|          |                                          |
|----------|------------------------------------------|
| ETIM 8.0 | EC000221 - Front element for push button |
|----------|------------------------------------------|