



#### General characteristics

|                          |                          |
|--------------------------|--------------------------|
| Colour                   | Yellow                   |
| Type of positions        | Extended pushbutton      |
| Material                 | Aluminium and zinc alloy |
| IEC degree of protection | IP66, IP67 and IP69K     |

#### Mechanical features

|                                           |        |                          |
|-------------------------------------------|--------|--------------------------|
| Mechanical life - spring return actuators | cycles | 5000000                  |
| Fixing                                    |        | Without mounting adapter |
| Mounting adapter                          |        | LPXAU120M                |


#### UL technical data

|                         |                              |
|-------------------------|------------------------------|
| UL degree of protection | Type1, 2, 3R, 4, 4X, 12, 12K |
|-------------------------|------------------------------|

#### Ambient conditions

|                       |     |    |     |
|-----------------------|-----|----|-----|
| Temperature           |     |    |     |
| Operating temperature |     |    |     |
|                       | min | °C | -25 |
|                       | max | °C | +70 |
| Storage temperature   |     |    |     |
|                       | min | °C | -40 |
|                       | max | °C | +85 |

#### Dimensions



#### Certifications and compliance

|              |                     |
|--------------|---------------------|
| Compliance   |                     |
|              | CSA C22.2 n° 14     |
|              | IEC/EN/BS 60947-1   |
|              | IEC/EN/BS 60947-5-1 |
|              | UL508               |
| Certificates |                     |
|              | cULus               |

#### ETIM classification

|          |                                          |
|----------|------------------------------------------|
| ETIM 8.0 | EC000221 - Front element for push button |
|----------|------------------------------------------|