



#### Electrical features

|                                               |          |         |
|-----------------------------------------------|----------|---------|
| Relay adj range                               | A        | 6.3-10  |
| IEC technical characteristics ( $\leq 440V$ ) |          |         |
|                                               | Ie<br>kW | A<br>kW |
|                                               | 10       | 3...4   |

#### Components

|                                     |          |
|-------------------------------------|----------|
| Starter enclosure standard supplied | M1RA     |
| Contactor standard supplied         | BF0910A  |
| Thermal relay standard supplied     | RF381000 |

#### UL technical data

|                         |                    |
|-------------------------|--------------------|
| UL degree of protection | Type 1, 12K, 4, 4X |
|-------------------------|--------------------|

#### Mechanical features

|        |   |     |
|--------|---|-----|
| Weight | g | 995 |
|--------|---|-----|

#### Ambient conditions

|                       |     |    |     |
|-----------------------|-----|----|-----|
| Operating temperature | min | °C | -25 |
|                       | max | °C | +60 |
| Storage temperature   | min | °C | -40 |
|                       | max | °C | +70 |

#### Resistance & Protection

|                          |      |
|--------------------------|------|
| IEC degree of protection | IP65 |
|--------------------------|------|

#### ETIM classification

|          |                                                                |
|----------|----------------------------------------------------------------|
| ETIM 8.0 | EC001037 -<br>Motor<br>starter/Motor<br>starter<br>combination |
|----------|----------------------------------------------------------------|