



#### Electrical features

|                                               |          |          |
|-----------------------------------------------|----------|----------|
| Relay adj range                               | A        | 24-32    |
| IEC technical characteristics ( $\leq 440V$ ) |          |          |
|                                               | Ie<br>kW | A<br>kW  |
|                                               |          | 32<br>15 |

#### Components

|                                     |          |
|-------------------------------------|----------|
| Starter enclosure standard supplied | M2PA     |
| Contactor standard supplied         | BF3200A  |
| Thermal relay standard supplied     | RF383200 |

#### UL technical data

|                                                       |           |    |                    |
|-------------------------------------------------------|-----------|----|--------------------|
| Maximum UL/CSA horsepower ratings single-phase        |           |    |                    |
|                                                       | 110V-120V | HP | 3                  |
|                                                       | 220V-240V | HP | 7.5                |
| Maximum UL/CSA horsepower ratings three-phase, 3-pole |           |    |                    |
|                                                       | 200V-208V | HP | 10                 |
|                                                       | 220V-240V | HP | 10                 |
|                                                       | 440V-480V | HP | 20                 |
|                                                       | 550V-600V | HP | 25                 |
| UL degree of protection                               |           |    | Type 1, 12K, 4, 4X |

#### Mechanical features

|        |   |      |
|--------|---|------|
| Weight | g | 1300 |
|--------|---|------|

#### Ambient conditions

|                       |     |    |     |
|-----------------------|-----|----|-----|
| Operating temperature |     |    |     |
|                       | min | °C | -25 |
|                       | max | °C | +60 |
| Storage temperature   |     |    |     |
|                       | min | °C | -40 |
|                       | max | °C | +70 |

#### Resistance & Protection

|                          |      |
|--------------------------|------|
| IEC degree of protection | IP65 |
|--------------------------|------|

#### ETIM classification

|          |                                                                |
|----------|----------------------------------------------------------------|
| ETIM 8.0 | EC001037 -<br>Motor<br>starter/Motor<br>starter<br>combination |
|----------|----------------------------------------------------------------|