P5ME4PS0630

MOULDED CASE CIRCUIT BREAKER THREE-POLE, IEC STANDARD, FOURTH POLE ON THE LEFT SIDE, 630A - ICU 65KA AT 400V



Electrical features			
Number of poles		Nr.	4
Rated current (≤40°C)		A	630
Electronic overload trip adjustment range		A	252…630
Electronic short circuit trip adjustment range		A	378…6300
AC rated operation voltage Ue		V	690
Rated insulation voltage Ui		V	1000
Rated impulse withstand voltage Uimp		kV	8
Short circuit breaking capacity Icu			
	220…240VAC 50/60Hz	kA	100
	380…415VAC 50/60Hz	kA	65
	440…460VAC 50/60Hz	kA	65
	480…500VAC 50/60Hz	kA	42
	525VAC 50/60Hz	kA	22
	660…690VAC 50/60Hz	kA	10
Short circuit breaking capacity Ics			
	220…240VAC 50/60Hz	kA	100
	380…415VAC 50/60Hz	kA	65
	440…460VAC 50/60Hz	kA	65
	480…500VAC 50/60Hz	kA	42
	525VAC 50/60Hz	kA	22
	660…690VAC 50/60Hz	kA	10
Heat dissipation per pole (max)		W	83
Mechanical features			
Terminals			
	screw		M10 x 30
	tool		Metric Allen key 8
Tightening torque for terminals			
	max	Nm	48
	max	lbin	425
Mounting position			
	normal		On vertical plan
	allowable		Any
Fixing			Screw
Weight		g	7200
Mechanical life		cycles	20000
Electrical life		cycles	6000
Dimensions (W x H x D)		mm	186x260x110
Ambient conditions			
Temperature			
	Operating temperature		
	min	°C	-20
	max	°C	+70
	Storage temperature		
	min	°C	-40

The characteristics described in this document are subject to updates or modifications at any time. The descriptions, technical and functional information, illustrations and instructions in this brochure are purely illustrative, and are consequently not contractually binding

P5ME4PS0630


MOULDED CASE CIRCUIT BREAKER THREE-POLE, IEC STANDARD, FOURTH POLE ON THE LEFT SIDE, 630A - ICU 65KA AT 400V

	max	°C	+80
Current derating for temperature >40°C			
	50°C	°C	591
	60°C	°C	555
	70°C	°C	517

Resistance & Protection

Frontal IP degree	IP20

Dimensions




Wiring diagrams

The characteristics described in this document are subject to updates or modifications at any time. The descriptions, technical and functional information, illustrations and instructions in this brochure are purely illustrative, and are consequently not contractually binding

P5ME4PS0630

MOULDED CASE CIRCUIT BREAKER THREE-POLE, IEC STANDARD, FOURTH POLE ON THE LEFT SIDE, 630A - ICU 65KA AT 400V



ETIM classification

EC000066 - Power contactor, AC switching

The characteristics described in this document are subject to updates or modifications at any time. The descriptions, technical and functional information, illustrations and instructions in this brochure are purely illustrative, and are consequently not contractually binding