



Auxiliary contact characteristics

Type of contact	2NO		
Rated insulation voltage Ui IEC/EN	V	300	
Rated impulse withstand voltage Uimp	kV	4	
UL/CSA and IEC/EN 60947-5-1 designation	C300 - R300		
Min. conductivity	5V 10mA		
Operating current AC15			
	24V	A	5
	48V	A	5
	60V	A	5
	110V	A	1.5
	230V	A	0.75
Operating current DC13			
	24V	A	1
	48V	A	1
	60V	A	0.5
	110V	A	0.22
	125V	A	0.22
	220V	A	0.11

Mechanical features

Tightening torque for terminals	min	Nm	1
	max	Nm	1
	min	lbin	9
	max	lbin	9
Conductor section	AWG/Kcmil		
	min	18	
	max	14	
Flexible w/o lug conductor section	min	mm ²	0.75
	max	mm ²	2.5
Flexible c/w lug conductor section	min	mm ²	0.75
	max	mm ²	2.5
Operating position	normal allowable	Vertical Any	
Terminals	type screw width tool	mm	Screw M3.5 7.2 Ph2
Weight		g	16

Operations

Mechanical life cycles 100000

Ambient conditions

Temperature

Operating temperature

min	°C	-20
max	°C	+60


Storage temperature

min	°C	-50
max	°C	+80

Max altitude	m	3000
--------------	---	------

IEC degree of protection	IP20
--------------------------	------

Wiring diagrams



Certifications and compliance

Compliance

CSA C22.2 n° 14
IEC/EN 60947-1
IEC/EN 60947-5-1
UL508

Certificates

cULus
EAC

ETIM classification