



Product designation			Illuminated selector switch actuator - 2 position		
Product type designation			LPCSL1204+LPXAU120		
General characteristics					
Colour			Red		
Type of positions			0 - 1		
IEC degree of protection			IP66, IP67 and IP69K		
Electrical characteristics					
Rated insulation voltage Ui IEC/EN			V	690	
IEC Conventional free air thermal current Ith			A	10	
Supply voltage (AC)			V	12...30	
Supply voltage (DC)			V	12...30	
Conductivity			1mA 5V		
UL/CSA and IEC/EN 60947-5-1 designation			A600 Q600		
Operating current AC15			12V	A	6
			24V	A	6
			48V	A	6
			120V	A	6
			240V	A	3
			400V	A	1.9
			480V	A	1.5
			500V	A	1.4
			600V	A	1.2
			Operating current DC13		
24V	A	3			
48V	A	1.5			
125V	A	0.55			
250V	A	0.27			
440V	A	0.15			
500V	A	0.13			
600V	A	0.1			
Contact resistance			mΩ	≤20	
Operations					
Electrical life			hours	100000	
Mechanical features					
Mechanical life			cycles	1000000	
Terminals screw			Screw		
Conductor section					
IEC			max	mm²	1 or 2 / 2.5
Mounting adapter					LPXAU120
UL technical data					
UL degree of protection					Type1, 2, 3R, 4, 4X, 12, 12K
Ambient conditions					
Temperature					
Operating temperature			min	°C	-25
			max	°C	+70
Storage temperature			min	°C	-40
			max	°C	+85
Certifications and compliance					
Compliance					
					CSA C22.2 n° 14
					IEC/EN/BS 60947-1
					IEC/EN/BS 60947-5-1
					UL508
Certificates					

KIT PLASTIC ILLUMINATED SELECTOR SWITCH ACTUATOR, 2 POSITION, 0 1. RED WITH
MOUNTING ADAPTER AND 2 CONTACT ELEMENTS, 1NO+1NC. SCREW TERMINATION. LED
INTEGRATED LAMP-HOLDER, STEADY LIGHT, 12...30VAC/DC

CCC

cULus

EAC

RINA