



#### Caratteristiche elettriche

Corrente d'impiego max ( $\leq 440V$ ) A 9

#### Caratteristiche dei contatti

Corrente di impiego Ie AC-3 ( $\leq 440V \leq 55^{\circ}C$ ) A 9

Potenza nominale AC-3 ( $T \leq 55^{\circ}C$ )	V	kW	Value
	230V	kW	2.2
	400V	kW	4
	415V	kW	4.3
	440V	kW	4.5
	500V	kW	5
	690V	kW	5

Contatti ausiliari incorporati

NA	0
NC	1

#### Dati tecnici UL

Maximum UL/CSA horsepower ratings single-phase

110V-120V	HP	0.5
220V-240V	HP	1.5

Maximum UL/CSA horsepower ratings three-phase, 3-pole


200V-208V	HP	2
220V-240V	HP	3
440V-480V	HP	5
550V-600V	HP	5

#### Caratteristiche meccaniche

Attacchi tipo Vite di fissaggio

Peso prodotto g 460

#### Dimensioni



### Schemi elettrici



### Omologazioni e conformità

Conformità

IEC/EN 60947-1

IEC/EN 60947-4-1

UL508 CSA C22.2 n° 14

Omologazioni

cULus

### Classificazione ETIM

ETIM 8.0

EC001037 -  
Combinazione  
starter motore