




Dati tecnici / Technical data

Installazione / Installation	segnapasso da interno	step light for indoor applications
Montaggio / Mounting	Line 2.0: a incasso (parete in muratura) Line 2.1: a incasso (parete in cartongesso)	Line 2.0: recessed (solid walls) Line 2.1: recessed (plasterboard)
Materiale / Material	corpo e ghiera in lamiera	body and trim in sheet metal
Finiture / Finishes	bianco, cor-ten, satinato	white, cor-ten, satin
N° e tipo LED / No. and type of LED	1 power LED	1 power LED
Potenza nomin. assorbita / Nom. power consumption	max 2W	max 2W
Alimentazione / Power supply	max 500mA	max 500mA
Alimentatore / Power supply unit	non incluso	not included
Cavi di alimentazione / Power cables	morsettiera	terminal block
Collegamento / Connection	in serie	series
Flusso totale apparecchio / Total delivered lumens	42 lm (3000K, 500mA)	42 lm (3000K, 500mA)
Ottiche / Optics	diffusa	diffuse
Colore LED / LED colour	bianco: 2700K, 3000K, 4000K, 5000K; blu	white: 2700K, 3000K, 4000K, 5000K; blue
Grado di protezione / Ingress protection	IP20	IP20
Classe di consumo energetico / Energy efficiency class	A / A+ / A++ (modulo LED integrato) in accordo con UE874/2012	A / A+ / A++ (built-in LED lamps) in accordance with EU/874/2012

Accessori / Accessories

Per installazione / For installation



WC1600 - Line 2.0
Cassaforma / Outer casing

Alimentatori / Power supply units

350mA	N° max prodotti / fixtures	PSU	IP	Pagina / Page	500mA	N° max prodotti / fixtures	PSU	IP	Pagina / Page
	1/3	A13350VL	20	593		1/3	A13500TC	20	593
	1/15	ACUNI020T1	20	592, 593, 595		1/10	ACUNI020T1	20	592, 593, 595
	2/6	A16350QL	20	593		2/5	A15500QL	20	593
	3/9	A19350QL	20	593		5/10	A310500QL	20	593
	5/12	A312350QL	20	593		1/12 Dimmer	ADUNITC	20	598, 599, 600
	1/12 Dimmer	ADUNITC	20	598, 599, 600					