Dati tecnici / Technical data

Installazione / Installation	incasso uplight da esterno (non adatto per immersione in piscine e fontane)	recessed uplight for outdoor applications (not suitable for immersion in swimming pools and fountains)
Montaggio / Mounting	a incasso (soffitto, parete, pavimento) spessore: min 3 mm, max 30 mm	recessed (ceiling, wall, floor) thickness: min 3 mm, max 30 mm
Materiale / Material	corpo e ghiera in acciaio inox AISI 316L schermo in vetro temprato	body and trim in AISI 316L stainless steel screen in tempered glass
N° e tipo LED / No. and type of LED	1 mid power LED	1 mid-power LED
Potenza nomin. assorbita / Nom. power consumption	0,6W (12Vdc), 1,2W (24Vdc), 0,5W (12Vac)	0,6W (12Vdc), 1,2W (24Vdc), 0,5W (12Vac)
Alimentazione / Power supply	12Vdc, 24Vdc, 12Vac	12Vdc, 24Vdc, 12Vac
Alimentatore / Power supply unit	non incluso	not included
Cavi di alimentazione / Power cables	incluso cavo in neoprene di 1,5 m H05RN-F 2x0,35 Ø6,3 mm	includes 1,5 m neoprene cable, H05RN-F 2x0,35 Ø6,3 mm
Flusso totale apparecchio / Total delivered lumens	20 lm (3000K, 24Vdc); 11 lm (3000K, 12Vdc)	20 lm (3000K, 24Vdc); 11 lm (3000K, 12Vdc)
Ottiche / Optics	diffusa	diffuse
Colore LED / LED colour	bianco: 2700K, 3000K, 4000K, 5000K	white: 2700K, 3000K, 4000K, 5000K
Grado di protezione / Ingress protection	IP68	IP68
Grado di resistenza / Impact resistance	IK10	IK10
Classe di consumo energetico / Energy efficiency class	A / A+ / A++ (modulo LED integrato) in accordo con UE874/2012	A / A+ / A++ (built-in LED lamps) in accordance with EU/874/2012

Accessori / Accessories

Per installazione / For installation



WC0201

Cassaforma / Outer casing



WC0202

Cassaforma / Outer casing

Cavi / Cables

WF0510

Cavo in neoprene /
Neoprene cable
H05RN-F 2x0,35 Ø6,3 mm
lunghezza a richiesta / your choice of length

WG0302

Molle di fissaggio / Fixing springs

Alimentatori / Power supply units

N° max prodotti / fixtures	PSU	IP	Pagina / Page
1...n	12Vdc	20	595
1...n	24Vdc	20	595
1...n	12Vdc	67	595
1...n	24Vdc	67	595