




Dati tecnici / Technical data

Installazione / Installation	incasso da esterno	recessed for outdoor applications
Montaggio / Mounting	a incasso (soffitto, parete, pavimento)	recessed (ceiling, wall, floor)
Materiale / Material	corpo in alluminio anodizzato, schermo in vetro temprato	body in anodized aluminium, screen in tempered glass
N° e tipo LED / No. and type of LED	1 power LED	1 power LED
Potenza nomin. assorbita / Nom. power consumption	max 2W	max 2W
Alimentazione / Power supply	max 500mA	max 500mA
Alimentatore / Power supply unit	non incluso	not included
Cavi di alimentazione / Power cables	incluso cavo in neoprene di 1,5 m H05RN-F 2x0,75/0,75 Ø6,3 mm	includes 1,5 m neoprene cable, H05RN-F 2x0,75/0,75 Ø6,3 mm
Collegamento / Connection	in serie	series
Flusso totale apparecchio / Total delivered lumens	108 lm (3000K, 500mA)	108 lm (3000K, 500mA)
Ottiche / Optics	10°, 20°, 46°, diffusa	10°, 20°, 46°, diffuse
Colore LED / LED colour	bianco: 2700K, 3000K, 4000K, 5000K	white: 2700K, 3000K, 4000K, 5000K
Grado di protezione / Ingress protection	IP67	IP67
Grado di resistenza / Impact resistance	IK08	IK08
Classe di consumo energetico / Energy efficiency class	A / A+ / A++ (modulo LED integrato) in accordo con UE874/2012	A / A+ / A++ (built-in LED lamps) in accordance with EU/874/2012

Accessori / Accessories

Antiabbagliamento / Anti-glare




WH0100* - Litus 1.0

Nido d'ape / Honeycomb louvre


* Da ordinare contestualmente all'apparecchio illuminante /
Order together with the lighting fixture

Per installazione / For installation




WC4010 - Litus 1.0

Cassaforma / Outer casing



WC4011 - Litus 1.1

Cassaforma / Outer casing



WC4511 - Litus 1.1

Cassaforma per cartongesso /
Outer casing for plasterboard



WL0200

Ventosa / Suction cup

Cavi / Cables

WF6005 - 5 m

WF6010 - 10 m

WF6015 - 15 m

WF6020 - 20 m

Cavi in neoprene /
Neoprene cables
H05RN-F 2x0,75/0,75
Ø6,3 mm
IPS

Alimentatori / Power supply units

350mA	N° max prodotti / fixtures	PSU	IP	Pagina / Page
	1/3	A13350VL	20	593
	1/15	ACUNI020T1	20	592, 593, 595
	2/6	A16350QL	20	593
	3/9	A19350QL	20	593
	5/12	A312350QL	20	593
	1/12 Dimmer	ADUNITC	20	598, 599, 600
	2/6	A16350IP67	67	593
	5/12	A312350IP67	67	593

500mA	N° max prodotti / fixtures	PSU	IP	Pagina / Page
	1/3	A13500TC	20	593
	1/10	ACUNI020T1	20	592, 593, 595
	2/5	A15500QL	20	593
	5/10	A310500QL	20	593
	1/12 Dimmer	ADUNITC	20	598, 599, 600
	1/4	A14500IP67	67	593
	5/10	A310500IP67	67	593