

## Data sheet

### 020LMV

Lampada spia monoblocco, BA9S, verde, alimentazione diretta



## Features

|                   |                                                             |
|-------------------|-------------------------------------------------------------|
| Range             | 020 Comando e Segnalazione SM2 Ø 22                         |
| Product           | Lampade spia Ø 22                                           |
| Type              | Monoblocco BA9S                                             |
| Item code         | 020LMV                                                      |
| Description       | Lampada spia monoblocco, BA9S, verde, alimentazione diretta |
| Colour            | Verde                                                       |
| Weight - gr       | 19,000                                                      |
| Custom tariff no. | 85365080                                                    |
| GTIN              | 8052878004637                                               |

## Technical data

|                           |                                                    |
|---------------------------|----------------------------------------------------|
| Approvals                 | CE, UL, CSA, EAC                                   |
| Compliance with standards | IEC-EN60947-1, IEC-EN60947-5-1, UL508, CSA C22-2   |
| Compliance with standards | UNI CEI EN 45545-2, CEI EN 61373                   |
| Operating temperatures    | -40° ÷ +70°C                                       |
| Protection degree         | IP66 - IP69K (IEC-EN60529 - DIN40050)              |
| Protection against impact | IK03 (IEC-EN62262)                                 |
| Shock resistance          | 30g duration=18ms (EN-IEC 60068-2-27)              |
| Shock resistance          | 50g duration=11ms (EN-IEC 60068-2-27)              |
| Vibration resistance      | 5g f= 2...500Hz (EN-IEC 60068-2-6)                 |
| Material                  | PA Polyamide                                       |
| Lens material             | PC Polycarbonate                                   |
| Locking ring material     | PA Polyamide                                       |
| Fixing diameter           | 22.5mm - Thickness 1÷6mm                           |
| Terminal screw            | Tightening torque 0.8÷1 Nm (IEC-EN60947-1)         |
| Terminal screw head shape | Combined:cross Phillips2 or slotted flat D.5mm max |
| Terminal screw material   | Zinc plated steel                                  |
| Tightening torque         | 1 ÷ 2,5Nm (8.8÷22.1 Lb-in)                         |
| Bulb type                 | Ba9S 400V - 2W max (not included)                  |
| Rated insulation voltage  | Ui 690V - Uimp 4KV (IEC-EN60947-1)                 |
| Overvoltage category      | Class II (IEC-EN61140)                             |
| Warranty period           | 18 months                                          |

## Data sheet

### 020LMV

Lampada spia monoblocco, BA9S, verde, alimentazione diretta

## Technical drawings

