

Data sheet

020PPLSG

Pulsante luminoso sporgente, stabile, giallo



Features

| | |
|-------------------|--|
| Range | 020 Comando e Segnalazione SM2 Ø 22 |
| Product | Pulsanti luminosi Ø 22 |
| Type | Sporgenti |
| Item code | 020PPLSG |
| Description | Pulsante luminoso sporgente, stabile, giallo |
| Colour | Giallo |
| Weight - gr | 20,000 |
| Custom tariff no. | 85365080 |
| GTIN | 8052878007621 |

Technical data

| | |
|---|--|
| Approvals | CE, UL, CSA, EAC |
| Compliance with standards | IEC-EN60947-1, IEC-EN60947-5-1, UL508, CSA C22-2 |
| Compliance with standards | UNI CEI EN 45545-2, CEI EN 61373 |
| Operating temperatures | -40° ÷ +70° C |
| Protection degree | IP66 - IP69K (IEC-EN60529 - DIN40050) |
| Protection against impact | IK03 (IEC-EN62262) |
| Mechanical durability | 500.000 Operations |
| Shock resistance | 30g duration=18ms (EN-IEC 60068-2-27) |
| Shock resistance | 50g duration=11ms (EN-IEC 60068-2-27) |
| Vibration resistance | 5g f= 2...500Hz (EN-IEC 60068-2-6) |
| Contact blocks configuration | Max no. 4 blocks (2+2) |
| Material | PA Polyamide |
| Button/mushroom material (illuminated type) | PC Polycarbonate |
| Locking ring material | ZAMAK zinc alloy |
| Fixing diameter | 22.5mm - Thickness 1÷6mm |
| Tightening torque | 2 ÷ 3Nm (17.7 ÷ 26.6 Lb-in) |
| Actuation type | Push-Push (maintained position) |
| Overvoltage category | Class II (IEC-EN61140) |
| Warranty period | 18 months |

Data sheet

020PPLSG

Pulsante luminoso sporgente, stabile, giallo

Technical drawings

