

## Data sheet

### 020PTAIBW

Pulsante con guardia, bianco, metallo



## Features

|                   |                                                |
|-------------------|------------------------------------------------|
| Range             | 020 Comando e Segnalazione SM2 Ø 22            |
| Product           | Pulsanti non luminosi Ø 22 - ghiera in metallo |
| Type              | Con guardia                                    |
| Item code         | 020PTAIBW                                      |
| Description       | Pulsante con guardia, bianco, metallo          |
| Colour            | Bianco                                         |
| Weight - gr       | 33,000                                         |
| Custom tariff no. | 85365080                                       |
| GTIN              | 8052878010751                                  |

## Technical data

|                                             |                                                  |
|---------------------------------------------|--------------------------------------------------|
| Approvals                                   | CE                                               |
| Compliance with standards                   | IEC-EN60947-1, IEC-EN60947-5-1, UL508, CSA C22-2 |
| Compliance with standards                   | UNI CEI EN 45545-2                               |
| Operating temperatures                      | -25° ÷ +65° C                                    |
| Protection degree                           | IP65 (IEC-EN60529)                               |
| Protection against impact                   | IK03 (IEC-EN62262)                               |
| Mechanical durability                       | 3.000.000 Operations                             |
| Shock resistance                            | 30g duration=18ms (EN-IEC 60068-2-27)            |
| Shock resistance                            | 50g duration=11ms (EN-IEC 60068-2-27)            |
| Vibration resistance                        | 5g f= 2...500Hz (EN-IEC 60068-2-6)               |
| Contact blocks configuration                | Max no. 6 blocks (3+3)                           |
| Button/mushroom material (illuminated type) | PC Polycarbonate                                 |
| External bezel material                     | Chromed zinc alloy                               |
| Locking ring material                       | ZAMAK zinc alloy                                 |
| Fixing diameter                             | 22.5mm - Thickness 1÷6mm                         |
| Tightening torque                           | 2 ÷ 3Nm (17.7 ÷ 26.6 Lb-in)                      |
| Actuation type                              | Spring return                                    |
| Overvoltage category                        | Class II (IEC-EN61140)                           |
| Warranty period                             | 18 months                                        |

## Data sheet

020PTAIBW

Pulsante con guardia, bianco, metallo

## Technical drawings

