


Data sheet

020PTF9MR

Pulsante a fungo sferico Ø 90, momentaneo, rosso



Features

Range	020 Comando e Segnalazione SM2 Ø 22
Product	Pulsanti di emergenza Ø 22
Type	Fungo sferico Ø 90, momentanei
Item code	020PTF9MR
Description	Pulsante a fungo sferico Ø 90, momentaneo, rosso
Colour	Rosso
Weight - gr	55,000
Custom tariff no.	85365080
GTIN	8052878013226

Technical data

Approvals	CE, UL, CSA, EAC
Compliance with standards	IEC-EN60947-1, IEC-EN60947-5-1, UL508, CSA C22-2
Compliance with standards	UNI EN ISO 13850, UNI EN ISO 12100, IEC-EN60947-5-5
Compliance with standards	UNI CEI EN 45545-2, CEI EN 61373
Operating temperatures	-40° ÷ +70°C
Protection degree	IP66 - IP69K (IEC-EN60529 - DIN40050)
Protection against impact	IK03 (IEC-EN62262)
Mechanical durability	3.000.000 Operations
Shock resistance	30g duration=18ms (EN-IEC 60068-2-27)
Shock resistance	50g duration=11ms (EN-IEC 60068-2-27)
Vibration resistance	5g f= 2...500Hz (EN-IEC 60068-2-6)
Contact blocks configuration	Max no. 6 blocks (3+3)
Material	PA Polyamide
Locking ring material	ZAMAK zinc alloy
Fixing diameter	22.5mm - Thickness 1÷6mm
Tightening torque	2 ÷ 3Nm (17.7 ÷ 26.6 Lb-in)
Actuation type	Spring return
Overvoltage category	Class II (IEC-EN61140)
Warranty period	18 months

Data sheet

020PTF9MR

Pulsante a fungo sferico Ø 90, momentaneo, rosso

Technical drawings

