

Data sheet

020SMLOV

Selettore luminoso a manopola, verde, 3 posizioni, Cam 0




Features

Range	020 Comando e Segnalazione SM2 Ø 22
Product	Selettori a manopola luminosi Ø 22
Type	3 posizioni
Item code	020SMLOV
Description	Selettore luminoso a manopola, verde, 3 posizioni, Cam 0
Colour	Verde
Weight - gr	27,000
Custom tariff no.	85365080
GTIN	8052878016326


Technical data

Approvals	CE, UL, CSA, EAC
Compliance with standards	IEC-EN60947-1, IEC-EN60947-5-1, UL508, CSA C22-2
Compliance with standards	UNI CEI EN 45545-2, CEI EN 61373
Operating temperatures	-40° ÷ +70° C
Protection degree	IP66 - IP69K (IEC-EN60529 - DIN40050)
Protection against impact	IK03 (IEC-EN62262)
Mechanical durability	1.000.000 Operations
Shock resistance	30g duration=18ms (EN-IEC 60068-2-27)
Shock resistance	50g duration=11ms (EN-IEC 60068-2-27)
Vibration resistance	5g f= 2...500Hz (EN-IEC 60068-2-6)
Contact blocks configuration	Max no. 2 blocks (1+1)
Material	PA Polyamide
Locking ring material	ZAMAK zinc alloy
Fixing diameter	22.5mm - Thickness 1÷6mm
Tightening torque	2 ÷ 3Nm (17.7 ÷ 26.6 Lb-in)
Overvoltage category	Class II (IEC-EN61140)
Warranty period	18 months

Technical drawings




CAM 0



020E10
020E10
020PD9

CAM 0



020E10
020E10
020PD9

